






Length	Width	Height	Un-Painted	Powder Coat	Nylon Coat
260	160	120	486-261612-66	487-261612*-66	488-261612*-66
Box Dimensions in mm			Colour Option - Colour suffix * - Grey= A / Blue= B / Black= E		




- Die cast aluminium enclosure sealed to  
BS EN 60529:1992 IP66, IP67
- 3mm One piece Die cut Silicone Rubber Sponge 01-255FR Seal
  - Seal has Self Adhesive Backing. 01-255SAB Suitable for -60 °c to 240 °c.
  - Min seal thickness 3.0mm - min seal frame width 3.5mm
  - Min enclosure wall thickness 3mm
  - Min enclosure lid thickness 3mm
  - PCB maximum dimensions 148mm Length, 1.7mm Width
  - Enclosures can be supplied Machined to your specifications
  - Made in the UK



Tel No. +44(0)1724 273200 Website [www.dem-uk.com](http://www.dem-uk.com)



PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF  
ALPHA 3 MANUFACTURING.  
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF  
ALPHA 3 MANUFACTURING IS PROHIBITED.



UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN MILLIMETRES.  
TOLERANCE:  
**NO DECIMAL PLACES ±0.2mm**  
**1 DECIMAL PLACE ±0.1mm**  
**2 DECIMAL PLACES ±0.05mm**  
**ANGULAR TOLERANCE: ±1°**

FINISH - See paint code for colour  
IF IN DOUBT ASK  
DO NOT SCALE DRAWING  
MATERIAL LM24 / LM2

DEBURR AND BREAK SHARP EDGES  
DRAWN BY SPB  
APPROVED BY WC  
THIRD ANGLE PROJECTION

SHEET 1 OF 1  
SCALE 1:4  
A4

TITLE  
**HEAVY DUTY  
DIE-CAST ENCLOSURE  
IP66**  
DRAWING NO.  
486-261612-66  
ISSUE  
**04**  
Release