

5-1571004 -5 Product Details


5-1571004 -5
[Active](#)

Slide Switches

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Number of Positions = 3
- ? Single Pole - Double Throw Configuration (Pole - Throw)
- ? Actuator Style = Side
- ? Actuator Color = Yellow
- ? SE Series

[View all Features](#) | [Find Similar Products](#)
[Live Product Chat](#) US Only
8:30am - 5pm ET, Mon - Fri

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [SWITCH, SLIDE, SURFACE MOUNT SE\(**\)SMT](#) (PDF, English)

Additional Information:

- ? [Product Line Information](#)

Catalog Pages/Data Sheets:

- ? None Available

Related Products:

- ? [Tooling](#)

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

[List all Documents](#)

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Number of Positions](#) = 3
- ? Configuration (Pole - Throw) = Single Pole - Double Throw
- ? Actuator Style = Side
- ? Mount Angle = Right Angle
- ? Grade = Instrumentation
- ? Termination Type = PC

Configuration Related Features:

- ? Terminal Configuration = Standard
- ? Operating Function = On Off On
- ? Number of Actuators = Single
- ? Process Seal Material = Silicone Rubber
- ? Terminals Connected = 1 -2, 2 -3

Electrical Characteristics:

- ? Contact Rating = 0.4VA

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Body Related Features:

- ? Actuator Color = Yellow
- ? Series = SE
- ? Mount Style = Surface Mount
- ? Switch Style = Process Sealed
- ? Actuator Material = Thermoplastic
- ? Flammability Rating = UL 94V -0
- ? Actuator Travel = 2.20 [.087]

Identification Marking:

- ? Stamped Marking = With

Contact Related Features:

- ? Contact Plating = Gold

Packaging Related Features:

- ? Packaging Method = Tape & Reel

Other:

- ? Brand = Tyco Electronics