



## SOLDER D-SUB CONNECTORS



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

### 37 Plug Solder Cup, Gold Flash

AMPLIMITE | Solder Cup Connectors

5-747916-2

TE Internal Number: 5-747916-2

Alias ID: 1364441

Always EU RoHS/ELV Compliant

Connector Style **Plug**

Number of Positions **37**

Contact Size **20**

Shell Size **4**

Enclosure **Without**

#### Product Drawings

[PLUG ASSEMBLY, SOLDER CUP, SIZE 4, 37 POSN, HD-20, AMPLIMITE](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[AMPLIMITE Subminiature D Connectors - Cable Connectors](#)

PDF  
English

#### Product Specifications

Product Specification

[AMPLIMITE HD-20 Subminiature D Solder Cup Plug And Receptacle Connectors](#)

PDF  
English

#### Product Environmental Compliance

TE Material Declaration

[MD\\_5-747916-2\\_0616201417\\_dmtec](#)

PDF  
English

#### Instruction Sheets

Instruction Sheet (U.S.)

[AMPLIMITE HDP-20 Connectors With Solder Cup Contacts](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	Connector Style	<b>Plug</b>
	Shell Size	<b>4</b>
	Product Type	<b>Connector</b>
	Shell Type	<b>Full Metal Shell</b>
	Grounding Indents	<b>With</b>
	Grade	<b>Standard</b>

---

Configuration Features	Number of Positions	<b>37</b>
	Preloaded	<b>Yes</b>

---

Body Features	Shell Plating Material	<b>Tin</b>
	Color	<b>Black</b>
	Insert Material	<b>Thermoplastic</b>
	Shell Material	<b>Steel</b>

---

Contact Features	Contact Size	<b>20</b>
	Contact Mating Area Plating Material	<b>Gold Flash</b>
	Contact Type	<b>Pin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Solder Tail Contact Plating Material	<b>Tin-Copper over Nickel</b>
	Contact Mating Area Plating Thickness (µin)	<b>.8</b>
	Contact Configuration	<b>Solder Cup</b>

---

Termination Features	Termination Method to Wire/Cable	<b>Solder</b>
----------------------	----------------------------------	---------------

---

Mechanical Attachment	Mating Connector Lock	<b>With</b>
	Mating Connector Lock Type	<b>Mounting Holes</b>
	PCB Mount Retention Type	<b>None</b>
	Mounting Angle	<b>Straight</b>

---

Housing Features	Enclosure	<b>Without</b>
------------------	-----------	----------------

---

Dimensions	Wire Range	<b>.5 – .6 mm<sup>2</sup> [ 20 AWG ]</b>
------------	------------	--

Industry Standards

Insert Flammability Rating

**UL 94V-0**

UL Flammability Rating

**UL 94V-0**

Packaging Features

Packaging Method

**Tray**

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

SOLDER D-SUB CONNECTORS	D-SUB BACKSHELLS & CLAMPS	WIRE-TO-BOARD CONNECTOR HOUSINGS	D-SUB LOCKING & MOUNTING
			
<p>37 Rcpt Solder Cup, Gold Flash 5-747917-2</p>	<p>2 PC STRAIN RELIEF KIT, 37P 5745081-1</p>	<p>20 MODIV HSG SR MRKD .100CL 3-87499-7</p>	<p>AMPLI FEM S'LOCK KIT 5747223-3</p>
<p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>			