










FEATURES	<ul style="list-style-type: none"> ■ <i>Dip solder tails single readout and double readout on .140" (3.56mm) row centers or .200" (5.08mm) row centers.</i> ■ <i>Solder eyelet, single readout and double readout on .200" (5.08mm) row centers.</i> ■ <i>Available with unique tails for PC board retention; holds the connector firmly on the board during wave soldering operations.</i> ■ <i>Bifurcated semi-bellows contacts for added contact reliability.</i> ■ <i>Ideal for applications involving vibration or board irregularities.</i> ■ <i>Contact positions: 6, 10, 12, 15, 18, 22, 24, and 25.</i> ■ <i>Accepts single- or double-sided .062" (1.59mm) thick PC boards.</i> ■ <i>Available less mounting ears or with .128" (3.25mm) mounting hole.</i> ■ <i>Meets applicable performance criteria of MIL-C-21097.</i> ■ <i>UL Recognized - file E170218 (UL1977) E130965 (UL1863).</i>
MATERIALS	<p>Insulation Material: UL 94V-0 rated glass-filled polyester, black</p> <p>Contact Material: Spring brass</p> <p>Contact Plating: 10μ" selective gold over 30μ" nickel in contact area, tin on tails</p>
ENVIRONMENTAL	<p>Shock: Per MIL-STD-202E, Method 213, Condition C</p> <p>Operating Temperature: -65°C to +105°C</p> <p>Vibration: Per MIL-STD-202E, Method 204, Condition B</p> <p>Humidity: Per MIL-STD-202, Method 103, Condition B</p> <p>Accessories:</p> <p>Polarizing Key: Two types (order separately):</p> <p>a) for between-contact polarization and</p> <p>b) for in-contact polarization</p> <p>See page 2-72 for more information.</p> <p>Card Guide Posts: (order separately):</p> <p>Attach to mounting ears and guide PC board into connector</p> <p>See page 2-72 for more information.</p>
ELECTRICAL	<p>Withstanding Voltage: 1800 VAC RMS (@ sea level)</p> <p>Current Rating: 5 Amps</p> <p>Contact Resistance: 6 Milliohms maximum</p> <p>Insulation Resistance: 5000 Megohms minimum</p>
MECHANICAL	<p>Individual Contact Insertion and Separation Force:</p> <p>16 oz. maximum with .070" (1.78mm) blade;</p> <p>1 oz. minimum with .054" (1.37mm) blade</p>



Marketed exclusively through distribution.



Dimensions

No. of Pos./Cont.	A		B		C		D	
	In	mm	in	mm	in	mm	in	mm
6/12	1.785	45.34	1.531	38.89	1.239	31.47	1.100	27.94
10/20	2.410	61.21	2.156	54.76	1.874	47.34	1.724	43.79
12/24	2.723	69.16	2.469	62.71	2.177	55.30	2.036	51.71
15/30	3.191	81.05	2.937	74.60	2.645	67.18	2.504	63.60
18/36	3.660	92.96	3.406	86.51	3.114	79.10	2.972	75.49
22/44	4.285	108.84	4.031	102.39	3.739	94.94	3.596	91.34
24/48	4.598	116.79	4.344	110.34	4.052	102.92	3.911	99.34
25/50	4.754	120.75	4.500	114.30	4.208	106.88	4.067	103.30

Ordering Information

No. of Pos./Cont.	Less Mounting Ears Catalog No.	.128 Mounting Hole Catalog No.
----------------------	-----------------------------------	-----------------------------------

Solder eyelet, single readout

6/6	50-6SN-8	50-6SN-7
10/10	50-10SN-8	50-10SN-7
12/12	50-12SN-8	50-12SN-7
15/15	50-15SN-8	50-15SN-7
18/18	50-18SN-8	50-18SN-7
22/22	50-22SN-8	50-22SN-7
24/24	50-24SN-8	50-24SN-7
25/25	50-25SN-8	50-25SN-7

Solder eyelet, double readout, .200" (5.08mm) row spacing

6/12	50-12SN-10	50-12SN-9
10/20	50-20SN-10	50-20SN-9
12/24	50-24SN-10	50-24SN-9
15/30	50-30SN-10	50-30SN-9
18/36	50-36SN-10	50-36SN-9
22/24	50-44SN-10	50-44SN-9
24/28	50-48SN-10	50-48SN-9
25/50	50-50SN-10	50-50SN-9

No. of Pos./Cont.	Less Mounting Ears Catalog No.	.128 Mounting Hole Catalog No.
----------------------	-----------------------------------	-----------------------------------

Dip solder tails, single readout, .156" (3.96mm) long

6/6	50-6SN-6	50-6SN-5
10/10	50-10SN-6	50-10SN-5
12/12	50-12SN-6	50-12SN-5
15/15	50-15SN-6	50-15SN-5
18/18	50-18SN-6	50-18SN-5
22/22	50-22SN-6	50-22SN-5
24/24	50-24SN-6	50-24SN-5
25/25	50-25SN-6	50-25SN-5

Dip solder tails, double readout, .200" (5.08mm) row spacing, .156" (3.96mm) long

6/12	50-12SN-3	50-12SN-1
10/20	50-20SN-3	50-20SN-1
12/24	50-24SN-3	50-24SN-1
15/30	50-30SN-3	50-30SN-1
18/36	50-36SN-3	50-36SN-1
22/44	50-44SN-3	50-44SN-1
24/48	50-48SN-3	50-48SN-1
25/50	50-50SN-3	50-50SN-1

No. of Pos./Cont.	Less Mounting Ears Catalog No.	.128 Mounting Hole Catalog No.
----------------------	-----------------------------------	-----------------------------------

Dip solder tails, double readout, .140" (3.55mm) row spacing, .125" (3.18mm) long

6/12	50-12SN-4	50-12SN-2
10/20	50-20SN-4	50-20SN-2
12/24	50-24SN-4	50-24SN-2
15/30	50-30SN-4	50-30SN-2
18/36	50-36SN-4	50-36SN-2
22/24	50-44SN-4	50-44SN-2
24/48	50-48SN-4	50-48SN-2
25/50	50-50SN-4	50-50SN-2

Dip solder tails with unique board retention feature .200" (5.08mm) row spacing, .156" (3.96mm) long

6/12	50-12SN-3R	50-12SN-1R
10/20	50-20SN-3R	50-20SN-1R
12/24	50-24SN-3R	50-24SN-1R
15/30	50-30SN-3R	50-30SN-1R
18/36	50-36SN-3R	50-36SN-1R
22/44	50-44SN-3R	50-44SN-1R
24/48	50-48SN-3R	50-48SN-1R
25/50	50-50SN-3R	50-50SN-1R

Marketed exclusively through distribution.