



MATERIALS:

Connector: 1st End – Phono Plug

Body and Center Contact – Brass

Finish: Body and Center contact – Nickel plated

Strain Relief Boot: PVC molded to Phone plug and cable. Color: Black

Cable: RG 174/U, 26 AWG, 7 x 34 T.C. Bare copperweld, vinyl insulated 2.54 (.100) O.D.

Color: Black

Marking: “POMONA ELECTRONICS 5092-K-XX”

Connector: 2nd End – Phono

Body and Center Contact – Brass

Finish: Body and Center contact – Nickel plated

Strain Relief Boot: PVC molded to Phone plug and cable. Color: Black

Cable: RG 174/U, 26 AWG, 7 x 34 T.C. Bare copperweld, vinyl insulated 2.54 (.100) O.D.

Color: Black

Marking: “POMONA ELECTRONICS 5092-K-XX”

RATINGS:

Operating Temperature: +50°C. (+122°F.) Max.

Operating Voltage: 500 VRMS

Nominal Impedance: 50 Ohms

Nom. Cap: 30.8 pF/FT.

ORDERING INFORMATION: Model 5092-K-XX

XX = Length in inches. Std. Lengths: 18” (45,72cm), 24” (60,96 cm), 36” (91,44 cm), 48” (121,92 cm). Additional lengths can be quoted upon request. Ordering Example: 5092-K-36, Cable length will be 36” (9,44mm) long.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02” (.51 mm), .xxx = ± .005” (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[5092-K-48](#) [5092-K-36](#) [5092-K-18](#) [5092-K-24](#)