



PCMCIA CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

136 MEMCD T/H STD HDR STACKED

[PC Card | H](#)

5146027-1

TE Internal Number: 5146027-1

[Always EU RoHS/ELV Compliant](#)

Connector Style **Header - Pin**

Header Type **Header Only**

Centerline **.64 mm [.025 in]**

Number of Positions **68**

Number of Rows **4**

Product Drawings

[STACKED PIN HEADER ASSEMBLY, 136 POSN, TOP BOARD MOUNTING, THRU-HOLE, AMP MEMORY CARD](#)

PDF [\(TIFF AVAILABLE\)](#)
English

[STACKED PIN HEADER ASSEMBLY, 136 POSN, TOP BOARD MOUNTING, THRU-HOLE, AMP MEMORY CARD](#)

PDF [\(TIFF AVAILABLE\)](#)
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Header - Pin

Applies To

Printed Circuit Board

Shielded

No

Product Type

Connector

Profile

Standard

Configuration Features	Number of Positions	68
	Number of Rows	4
	Number of Slots	2
	Preloaded	Yes
	Lead Configuration	Staggered
Electrical Characteristics	Voltage (VAC)	5
Body Features	Header Type	Header Only
	Hold-Downs	Without
	Color	Black
Contact Features	Contact Type	Pin
	Underplate Material	Nickel
	Solder Tail Contact Plating Material	Tin
	Contact Base Material	Brass
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µin)	30
Mechanical Attachment	PCB Mounting Style	Through Hole
	Mounting Angle	Right Angle
	Mating Alignment	Without
	Board Mount	Top Side
Housing Features	Centerline	.64 mm [.025 in]
	Housing Material	LCP (Liquid Crystal Polymer)
Dimensions	Height above PC Board (mm)	9.6
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	20
	Packaging Method	Tray, Tray/Box
Other	Comment	Two size M2 screws (customer supplied) are required for strain relief.

