



# CRIMP RINGS & SPADES



Active

PRODUCT DRAWING  
English

3D PDF

## TE CONNECTIVITY (TE) TERMINAL,PIDG R IR 18 6 PIDG

51863-4  
TE Internal Number: 51863-4  
Mil-Spec: M7928/1-31

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue**

Stud Diameter **3.68 mm [ .145 in ]**

Tongue Thickness **.79 mm [ .031 in ]**

Heavy Duty **No**

Wire Insulation Diameter (Max) (in) **.125**

### Product Drawings

[TERMINAL, RING TONGUE, PIDG WIRE SIZE: 22-16 AWG](#)  
PDF  
English

### CAD Files

[3D PDF](#)  
PDF  
3D  
  
[Customer View Model](#)  
2D\_DXF.ZIP  
English  
  
[Customer View Model](#)  
3D\_GS.ZIP  
English  
  
[Customer View Model](#)  
3D\_STP.ZIP  
English

### Product Specifications

Application Specification [Pre-Insulated Diamond Grip \(PIDG\) Terminals, Splices, And End Caps](#)  
PDF  
English

### Product Environmental Compliance

TE Material Declaration [MD\\_51863-4\\_05022015455\\_dmtec](#)  
PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Barrel Type

**Closed Barrel**

Wire/Cable Type

**Regular Wire**

	Insulated	<b>Yes</b>
	Insulated Wire Support	<b>Yes</b>
	Support Style	<b>Insulation Restriction</b>
	Stud Size	<b>6, M3.5</b>
	Shape Code	<b>RING-042</b>
	Barrel Style	<b>Standard</b>
	Wire/Cable Composition	<b>Solid or Stranded</b>
Configuration Features	Terminal Angle	<b>Straight</b>
	Number of Holes	<b>1</b>
Electrical Characteristics	Voltage (Max) (V)	<b>300</b>
Body Features	Plating Material	<b>Copper, Tin</b>
	Insulation Sleeve Material	<b>Copper</b>
	Insulation Sleeve Color	<b>Red</b>
	Insulation Material	<b>Nylon</b>
	Weight per Piece (g)	<b>.767</b>
	Stripe Color	<b>White</b>
Contact Features	Terminal Shape	<b>Ring Tongue</b>
	Terminal Orientation	<b>Straight</b>
	Class	<b>1 &amp; 2</b>
Dimensions	Stud Diameter	<b>3.68 mm [ .145 in ]</b>
	Tongue Thickness	<b>.79 mm [ .031 in ]</b>
	Wire Insulation Diameter (Max) (in)	<b>.125</b>
	Wire Insulation Diameter	<b>1.42 – 2.79 mm [ .056 – .11 in ]</b>
	Wire Size (AWG)	<b>18</b>
	Wire Size (mm <sup>2</sup> )	<b>.8 – .9</b>
	Wire Size (CMA)	<b>1900</b>
	Barrel Inside Diameter (in)	<b>.28</b>
	Overall Length	<b>19.86 mm [ .782 in ]</b>
Operation/Application	Heavy Duty	<b>No</b>

Industry Standards	Government Qualified	<b>Yes</b>
Packaging Features	Packaging Method	<b>Loose Piece</b>
	Packaging Quantity	<b>1000</b>
Other	Barrel Color	<b>Red</b>
Product Compliance	<a href="#">Statement of Compliance PDF</a> <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

## CUSTOMERS ALSO BOUGHT

<p><b>TERMINAL BLOCK HEADERS &amp; RECEPTACLES</b></p>  <p><b>4 POS TERMI-BLOK HDR VERTICAL</b> 796867-4</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>TERMINAL BLOCK HEADERS &amp; RECEPTACLES</b></p>  <p><b>5 POS TERMI-BLOK HDR DIR. POL.</b> 284514-5</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>HEAT SHRINK TUBING</b></p>  <p><b>VERSAFIT-1/4-0-STK</b> VERSAFIT-1/4-0-STK</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>CRIMP RINGS &amp; SPADES</b></p>  <p><b>TERMINAL, PIDG RECT 16-14 6</b> 2-327958-4</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>
---	--	--	---