



RJ45 CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) INV MJ ASSY, 1X2

Mini PCI , Multi IO

5406526-1
TE Internal Number: 5406526-1

Always EU RoHS/ELV Compliant

Port Configuration **Multiple**

Shielded **No**

Jack Configuration **1 x 2**

Connector Style **Jack**

Inverted Jack Face **Yes**

Product Drawings

[INVERTED MOD JACK ASSEMBLY, 1x2](#)

PDF (TIFF AVAILABLE)
English

[INVERTED MOD JACK ASSEMBLY, 1x2](#)

PDF (TIFF AVAILABLE)
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Product Specification

[High Performance Modular Plugs & Jacks, PCB Mounted](#)

PDF
English

Application Specification

[Modular Jacks](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_5406526-1_03052014823_dmtec](#)

PDF
English

Product Type Features	Shielded	No
	Connector Style	Jack
	Performance Category	Cat 5
	Profile	Standard
	PCB Mounting Orientation	Side Entry (Right Angle)
	Product Type	Connector
	Jack Type	RJ45
	Grounding Options	Without
	Connector Type	Connector Assembly
	LED	Without
Panel Stops	Without	

Configuration Features	Port Configuration	Multiple
	Jack Configuration	1 x 2
	Number of Positions	8
	Keyed	No
	Preloaded	Yes

Body Features	Inverted Jack Face	Yes
	Color	Black

Contact Features	Number of Contacts Loaded	8
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µin)	15


Termination Features	Termination Method to PC Board	Solder
----------------------	--------------------------------	---------------

Mechanical Attachment	PCB Mounting Style	Through Hole
	Panel Mount Retention	Without

Housing Features	Housing Material	High Temperature Thermoplastic
	Housing Color	Black

Dimensions	PCB Tail Length	2.54 mm [.1 in]
	Height (in)	.505
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	72
	Packaging Method	Tray, Tray/Box
Other	Comment	Recommended applications: Fast Ethernet, 10Base-T Ethernet, and 10/100 Base-T Ethernet (Cat 5 on two pair 1/2, 3/6).
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

RIBBON CABLE CONNECTORS	WIRE-TO-BOARD HEADERS & RECEPTACLES	SMA CONNECTORS	RECTANGULAR POWER CONNECTORS
 <p>26 WAY GREY MK II RECP 2-215882-6</p> <p>Save to List Find Similar Products</p>	 <p>DYNAMIC D-5200 HDR ASSY 6P V X 1-179960-3</p> <p>Save to List Find Similar Products</p>	<p>SMA R/A PCB SKT GB 3-1478978-1</p> <p>Save to List Find Similar Products</p>	<p>MICRO MNL RFECEPT HSC SINGLE R 1445022-3</p> <p>Save to List Find Similar Products</p>