




PCB D-SUB CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

RCPT ASSY, LPF, 24 POS, R/TANG

CHAMP | CHAMP

5555139-2

TE Internal Number: 5555139-2

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Centerline **2.16 mm [.085 in]**

Number of Positions **24**

Profile **Low**

PCB Mounting Orientation **Right Angle**

Product Drawings

RECEPTACLE ASSEMBLY, 24 POSITION, RIGHT ANGLE, SHIELDED, LOW PROFILE, WITH GROUNDING BRACKET, CHAMP

PDF (TIFF AVAILABLE)
English

RECEPTACLE ASSEMBLY, 24 POSITION, RIGHT ANGLE, SHIELDED, LOW PROFILE, WITH GROUNDING BRACKET, CHAMP

PDF (TIFF AVAILABLE)
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Product Specifications

Application Specification

CHAMP Printed Circuit (PC) Board Mounted Connectors

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Receptacle

Profile

Low

	PCB Mounting Orientation	Right Angle
	Applies To	Printed Circuit Board
	Grounded	Yes
	Orientation	Standard
	Product Type	Connector
	Shielded	Yes
Configuration Features	Number of Positions	24
	Preloaded	Yes
Body Features	Plating Material	Polyester
	Shield Plating Material	Nickel over Copper
	Ground Bracket Material	Carbon Steel
	Color	Black
	Ground Bracket Plating Material	Tin
	Shield Plating Finish	Bright
	Shield Material	Die Cast Metal
Contact Features	Solder Tail Contact Plating Material	Tin
	Contact Base Material	Copper Alloy
	Contact Mating Area Plating Thickness (µin)	30
	Contact Mating Area Plating Material	Gold
Mechanical Attachment	PCB Mount Retention	With
	PCB Mount Retention Type	Boardlocks
	Mating Connector Lock	With
	Mating Connector Lock Type	Screwlocks
	Panel Mount Retention	With
	Screw Size	14702
	Panel Attachment Style	Rear Mount
Housing Features	Centerline	2.16 mm [.085 in]
	Housing Color	Black
	Housing Material	Polyester GF
Dimensions	PCB Thickness (Recommended)	1.57 mm [.062 in]

Packaging Features	Packaging Method	Tube
	Packaging Quantity	10
Other	Comb Material	Polyester

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

HIGH FREQUENCY & RF INDUCTORS



SC30-10-2510-10 0.56UH
AMMO 1000
SC30R56KT

Save to List

Find Similar Products

USB CONNECTORS



Mini USB AB R/A, Rcpt,
SMT, T&R, 0.6mm
1-1734328-2

Save to List

Find Similar Products

IDC D-SUB CONNECTORS



EMI RCPT ASSY, 24 POSN,
SHLD
5554434-1

Save to List

Find Similar Products

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



02 MODII HDR SRST
UNSHRD .100
87224-2

Save to List

Find Similar Products