

RJ45 CONNECTORS



TE CONNECTIVITY (TE) STK MJ ASSY,8POS,2X3,SHLD,CAT5

Mini PCI , SKT

5569256-1

TE Internal Number: 5569256-1

Always EU RoHS/ELV Compliant

Port Configuration **Stacked**

Shielded **Yes**

Jack Configuration **2 x 3**

Connector Style **Jack**

Inverted Jack Face **No**

✓ Active

 **PRODUCT DRAWING**

English

 **3D PDF**

Product Drawings

STACKED MODULAR JACK ASSEMBLY, 2 X 3 PORT, 8 POSITION, SHIELDED, PRINTED CIRCUIT BOARD GROUND, CATEGORY 5

[PDF \(TIFF AVAILABLE\)](#)

English

STACKED MODULAR JACK ASSEMBLY, 2 X 3 PORT, 8 POSITION, SHIELDED, PRINTED CIRCUIT BOARD GROUND, CATEGORY 5

[PDF \(TIFF AVAILABLE\)](#)

English

CAD Files

Customer View Model

2D_DXF.ZIP

English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

3D PDF

PDF

English

Catalog Pages/Data Sheets

82066 Modular Jacks And MRJ21 Product Catalog - Stacked Modular Jacks Section

PDF

English

Product Specifications

Product Specification

High Performance Modular Plugs & Jacks, PCB Mounted

PDF

English

Application Specification

Modular Jacks

PDF

English

Drawing for all design activity.

Product Type Features	Shielded	Yes
	Connector Style	Jack
	Performance Category	Cat 5
	Profile	Low
	PCB Mounting Orientation	Side Entry (Right Angle)
	Connector Type	Connector Assembly
	Applies To	Printed Circuit Board
	Product Type	Connector
	Jack Type	RJ45
	Grounding Options	PCB Ground
	LED	Without
	Panel Stops	Without

Configuration Features	Port Configuration	Stacked
	Jack Configuration	2 x 3
	Number of Positions	8
	Terminals per Port	8
	Number of PCB Ground Tabs	8
	Preloaded	Yes
	Keyed	No

Body Features	Inverted Jack Face	No
	Shield Material	Copper Alloy
	Grounding Tab Plating Material	Tin over Copper
	Color	Black
	Shield Plating Material	Tin over Copper

Contact Features	Number of Contacts Loaded	8
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze
	PCB ACTION PIN Grounds	Without
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (μin)	50

Termination Features	Grounding Clips	Without
----------------------	-----------------	----------------

TERMINATION FEATURES

Grounding Clips

WIRELESS

Termination Method to PC Board

Solder

Mechanical Attachment

PCB Mounting Style

Through Hole

Panel Mount Retention

Without

Housing Features

Housing Material

PCT Polyester

Housing Color

Black

Dimensions

Height (mm)

25.27

PCB Thickness (Recommended)

1.57 mm [.062 in]

PCB Tail Length

3.56 mm [.14 in]

Industry Standards

UL Flammability Rating

UL 94V-0

Product Compliance

[Statement of Compliance](#)

PDF

[VIEW ALL PRODUCT COMPLIANCE](#)