

SPECIFICATION CONTROL DRAWING

55A6373TITLE
TWO CONDUCTOR CABLE, SILVER-COATED HIGH STRENGTH
COPPER ALLOY, UNSHIELDED, UNJACKETED, 600 VOLTDate
5-14-93Revision
B

This specification sheet forms a part of the latest issue of Raychem Specification 55A.

COMPONENT WIRES - 55A6359



CABLE CONSTRUCTION DETAILS				
PART NUMBER	CONDUCTOR SIZE (AWG)	OUTSIDE DIAM- ETER (inches)		MAXIMUM WEIGHT (lbs/1000 ft.)
		NOMINAL	MAXIMUM	
55A6373-28-*	28	.054	.058	1.9
55A6373-26-*	26	.064	.068	2.8
55A6373-24-*	24	.074	.078	4.0
55A6373-22-*	22	.086	.090	5.8

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms)

* BLOCKING: 200 ± 3°C for 6 hours

DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz

* FLAMMABILITY:

Procedure 1, 3 seconds (maximum); 3 inch
(maximum); no flaming of facial tissue

PART NUMBER:

The "*" in the part numbers above shall be
replaced by a color code designator with a
slash separating the component wire colors.Example: AWG 28, white and black component
wires: 55A6373-28-9/0

* Qualification Test

NOTE: Nominal values are for information only.
Nominal values are not requirements.

COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-881.

DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.

RaychemRaychem Corporation
300 Constitution Drive, Menlo Park, California 94025
(415) 361 3333 TWX 910 373 1728

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[55A6373-28-0/9CS2063](#)