



- Circuit Board Indicators
- Panel Mount Indicators
- Solid State Lighting
- Traffic Signals
- Vehicle Lighting
- Rail
- Obstruction Lighting
- Hazardous Area Lighting
- Heliport Lighting

how to purchase

-  [sales contacts](#)
-  [stock check](#)

search

 **Product Line Search**

Please select a Product Line to search.

Part # / Text Search

Part No.:

Text Search:

quick links

Dialight Corporate Video


Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes FAQs

**Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives**

Circuit Board Indicators - Through Hole Indicators	
P/N# 5600301F	Bi-Pin LED Lamp Single Color
Description	Bi Pin LED Lamp
Package Options	25 Pieces Per Bag
Product Type	onlinecomponents.com THE ONLINE DISTRIBUTOR OF ELECTRONIC COMPONENTS Through Hole Indicators
Sub Product Type	Discrete LED
Configuration	Bi-Pin LED Lamp
Lamp Type	Single Color
Viewing	Top View
Viewing Angle	70
Test Current (mA)	10mA

Absolute Maximum Ratings (Ta = 25 °)	
Reverse Current	10 @ Vr = 12
Derating	from 46Â° @ .74 A/Â°C
Solder Temp	230Â° for 7 sec
Operating Temp	-55 to +100° C
Storage Temp	-55 to +100° C



Operating Characteristics	
LED Position	
Color	Yellow
Lamp Type	Single Color
LED Type	High Efficiency
Intensity Min (mcd)	4.5
Intensity Typ (mcd)	
Intensity Max (mcd)	28.0
Fwd Voltage Min	
Fwd Voltage Typ	
Fwd Voltage Max	
Dom Wavelength Min (nm)	587
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	130
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Distributor Stock Check

Check stock with our distributors now.

5600301F