



- Circuit Board Indicators
- Panel Mount Indicators
- Solid State Lighting
- Traffic Signals
- Vehicle Lighting
- Rail
- Obstruction Lighting
- Hazardous Area Lighting
- Heliport Lighting

- how to purchase
 -  sales contacts
 -  stock check

 search

 Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

find

Part # / Text Search

Part No.:

Text Search:

 quick links

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes
FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives

Circuit Board Indicators - Through Hole Indicators

P/N# 5640100932F

onlinecomponents.com

3 mm Lens

Description

Package Options

Product Type

Sub Product Type

Configuration

Viewing

Viewing Angle

Test Current (mA)

3 mm Tri-Level CBI B-Y-G

5 Pieces Per Bag

Through Hole Indicators with Tri-Level Housing

3 mm Lens

Right Angle

60

10mA

Absolute Maximum Ratings (Ta = 25 °)

Solder Temp

Operating Temp

Storage Temp

260Å° for 5 sec

-55 to +100° C

-55 to +100° C



Operating Characteristics				
LED Position	Found in position(s): 1	Found in position(s): 2	Found in position(s): 3	
Color	Blue	Yellow	Green	
Lamp Type	Single Color	Single Color	Single Color	
LED Type	Standard Efficiency	Standard Efficiency	Standard Efficiency	
Intensity Min (mcd)	7.1	7.4	4.7	
Intensity Typ (mcd)	12.5	10.0	12.6	
Intensity Max (mcd)	18			
Fwd Voltage Min				
Fwd Voltage Typ				
Fwd Voltage Max				
Dom Wavelength Min (nm)	465			
Dom Wavelength Typ (nm)				
Dom Wavelength Max (nm)				
Power Dissipation Max (mW)	90	60	100	
Backlighting				
Pitch Between Vertical				
Pitch Between Horizontal				
Lum Intensity Min				
Lum Intensity Typ				
Lum Intensity Max				

Distributor Stock Check

Check stock with our distributors now.

5640100932F

check stock