



- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

| Circuit Board Indicators - Through Hole Indicators | |
|--|--------------------------------|
| P/N# 5690302222F | 3 mm Lens Single Color |
| Description | 3 mm Dual Bi-Level CBI G-G-G-G |
| Package Options | 50 Pieces Per Bag |
| Product Type | Through Hole Indicators |
| Sub Product Type | with Bi-Level Housing |
| Configuration | 3 mm Lens |
| Lamp Type | Single Color |
| Viewing | Right Angle |
| Viewing Angle | 60 |
| Test Current (mA) | 5V |

| Absolute Maximum Ratings (Ta = 25 °) | |
|--------------------------------------|--------------------------------|
| Reverse Current | 100 @ Vr = 5V |
| Derating | from 50A° @ 0.086 V/A°C |
| Reverse Voltage | 5 V |
| Solder Temp | 260A° for 5 sec |
| Operating Temp | -40 to +85° C |
| Storage Temp | -55 to +100° C |

Distributor Stock Check

Check stock with our distributors now.

[check stock](#)

- how to purchase
- sales contacts
 - stock check
- search
- Product Line Search

Please select a Product Line to search.

[find](#)

Part # / Text Search

Part No.:

Text Search:

[search](#)

quick links

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives



Operating Characteristics

| | |
|----------------------------|-------------------|
| LED Position | 1-4 |
| Color | Green |
| Lamp Type | Single Color |
| LED Type | Integral Resistor |
| Intensity Min (mcd) | 5.6 |
| Intensity Typ (mcd) | 19.0 |
| Intensity Max (mcd) | |
| Fwd Voltage Min | |
| Fwd Voltage Typ | |
| Fwd Voltage Max | |
| Dom Wavelength Min (nm) | |
| Dom Wavelength Typ (nm) | |
| Dom Wavelength Max (nm) | |
| Power Dissipation Max (mW) | |
| Backlighting | |
| Pitch Between Vertical | 4.57 |
| Pitch Between Horizontal | |
| Lum Intensity Min | |
| Lum Intensity Typ | |
| Lum Intensity Max | |