



PCB D-SUB CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) HD-20 PLUG 9P VERT FFSCRLK AMPLIMITE | Standard

5745071-4
TE Internal Number: 5745071-4

Always EU RoHS/ELV Compliant

Connector Style **Plug**

Centerline (in) **.109**

Number of Positions **9**

Number of Rows **2**

Shell Size **1**

Product Drawings

[PLUG ASSEMBLY, SIZE 1, 9 POSN, VERTICAL, AMPLIMITE HD-20](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[AMPLIMITE Subminiature D Connectors - Straight Posted Connectors](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_5745071-4_09152011130](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Plug

Shell Size

1

Standard

Standard

Profile	Standard
PCB Mounting Orientation	Vertical
Grounding Straps	Without
Shell Type	All Plastic
Grounding Indents	Without
Applies To	Printed Circuit Board
Sealed	No
Grounded	No
Product Type	Connector
Shielded	No

Configuration Features	Number of Positions	9
	Number of Rows	2
	Preloaded	Yes

Body Features	Plastic	Yes
	Female Screwlock Material	Brass
	Female Screwlock Plating Material	Nickel over Copper Flash
	Color Code	None
	Post Size	.66 mm [.026 in]

Contact Features	Contact Shape	Round
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Brass
	Contact Mating Area Plating Thickness (µin)	30
	Contact Mating Area Plating Material	Gold


Termination Features	Termination Post Length	4.32 mm [.17 in]
	Grounding Clips	Without

Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	With
	PCB Mount Retention Type	Mounting Holes
	Mating Connector Lock	With
	Mating Connector Lock Type	Female Screwlocks, Fixed
	Panel Mount Retention	Without
	Mounting Hole Diameter	3.05 mm [.12 in]

Housing Features	Centerline (in)	.109
	Housing Color	Black
	Housing Material	Polyester
Dimensions	PCB Thickness (Recommended)	2.36 – 3.18 mm [.093 – .125 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Tube
	Packaging Quantity	17
Other	Comment	Plugs are preloaded with size 20 DF posted pin contacts

Product Compliance [Statement of Compliance PDF](#)
[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

PCB D-SUB CONNECTORS	PCB D-SUB CONNECTORS	PCB D-SUB CONNECTORS	CIRCUIT BREAKERS
			
09 PLUG SP/AP SCRLK 745071-4	HD-20 PLUG 37P VERT FFSCRLK 5745074-4	HD-20 RCPT 37P VERT FFSCRLK 5745079-6	W33-S4B1Q-10=W33 W33-S4B1Q-10
Save to List Find Similar Products			

Products - 3 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors
AMPLIMITE I HDE (IDC) Insulation

09 HDE AP RECEPT, LEAD FREE - 745201-7

TE INTERNAL NUMBER: 745201-7

✓ Active

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Number of Positions **9**

Number of Rows **2**

Preloaded **Yes**

Contact Size **20**



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors
AMPLIMITE I HDF for Flat Ribbon Cable

09 POS HDF RCPT, AP, LEAD FREE - 1658614-4

TE INTERNAL NUMBER: 1658614-4

✓ Active

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Number of Positions **9**

Number of Rows **2**

Preloaded **Yes**

Contact Size **20**



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors
AMPLIMITE I HDF for Flat Ribbon Cable

09 POS HDF RCPT, AP, LEAD FREE - 1658609-4

TE INTERNAL NUMBER: 1658609-4

✓ Active

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Number of Positions **9**

Number of Rows **2**

Preloaded **Yes**

Contact Size **20**

