

Dialight - Leader in LED Technology



- ?

[Circuit Board Indicators](#)

?

[Panel Mount Indicators](#)

?

[Solid State Lighting](#)

?

[Traffic Signals](#)

?

[Vehicle Lighting](#)

?

[Rail](#)

?

[Obstruction Lighting](#)

?

[Hazardous Area Lighting](#)

?

[Heliport Lighting](#)

Region:
Product Line:

Circuit Board Indicators

Check stock with our distributors now.

5977702602F

Please note that the stock check**is only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.

Please select a Product Line to search.

Circuit Board Indicators

Part No.:

Text Search:

[Dialight Corporate Video](#)

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp.
[View PDF File](#)

[Application Notes](#)
[FAQs](#)

[Dialight Ltd \(UK\)](#)
[Dialight Garufo](#)
[Dialight BLP](#)
[LumiDrives](#)

menu rendered

Circuit Board Indicators - Surface Mount Indicators	
P/N# 5977702602F	1210 Package Bi - Color
Description	

Solder Temp
Operating Temp
Storage Temp

260Â° fo 5 sec
-55~+100° C
-55~+100° C

RoHS Compliai Product

Distributor Stock Check

Check stock with our distributors now.

5977702602F

Operating Characteristics	
LED Position	
Color	Red / Green
Lamp Type	Bi-Color / Bi-Color
LED Type	
Intensity Min (mcd)	3.6 / 9.0
Intensity Typ (mcd)	6.3 / 16.0
Intensity Max (mcd)	9 / 23
Fwd Voltage Min	2.0 / 2.2
Fwd Voltage Typ	2.8 / 2.8
Fwd Voltage Max	
Dom Wavelength Min (nm)	653 / 575
Dom Wavelength Typ (nm)	100 / 100
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	