



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

RJ45 OVER USB W/ LED G/Y 30u" Au

A-RJ45

6-1775855-3

TE Internal Number: 6-1775855-3

Always EU RoHS/ELV Compliant

Port Configuration **Stacked**

Jack Type **RJ45 over Single USB**

Performance Category **Cat 3**

PCB Mounting Style **Through Hole**

Profile **Standard**

Product Drawings

[Modular Jack RJ45 Stacked Over USB Conn. Dip Type](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Jack Type	RJ45 over Single USB
Performance Category	Cat 3
Profile	Standard
Shielded	Yes
LED	With
Panel Stops	Without
PCB Mounting Orientation	Right Angle
Product Type	Connector

	Grounding Options	Panel Ground and PCB Ground
	Connector Style	Jack
	Multi-Port Modular Jack	No
Configuration Features	Port Configuration	Stacked
	Jack Configuration	2 x 1
	Number of Positions	8
	Preloaded	Yes
	Number of PCB Ground Tabs	4
	Keyed	No
Body Features	Color	Black
	Shield Material	Brass
	Inverted Jack Face	No
	Shield Plating Material	Nickel
Contact Features	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Gold Flash over Nickel
Termination Features	Termination Method to PC Board	Solder
Mechanical Attachment	PCB Mounting Style	Through Hole
	Panel Mount Retention	Without
Housing Features	Housing Material	PBT GF
Dimensions	PCB Tail Length	3.5 mm [.138 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Tray, Tray/Box
	Packaging Quantity	50
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

