

## CATALOG

## ➔ Cross Reference

[Competitive Products](#)  
[Military Spec P/Ns](#)  
[Tyco Brand P/Ns](#)

- ➔ [Part Number Search](#)
- ➔ [Document Search](#)
- ➔ [Product Type Search](#)
- ➔ [Product Family Search](#)
- ➔ [Alphabetical Search](#)
- ➔ [RoHS/ELV Compliance & Alternates](#)
- ➔ [CAD Model Search](#)
- ➔ [Brand Search](#)
- ➔ [Tool Search](#)
- ➔ [Multiple Part Comparison](#)
- ➔ [Lead Free Solutions](#)
- ➔ [Help/Glossary](#)

[Home](#)e-bulletin newsletter  
**SUBSCRIBE NOW!**  
click here

## Soft Shell Connectors

## ➔ Soft Shell - Contacts

**61366-1**  Active**Directive 2002/95/EC  
Compliant**RoHS Compliant**(Corporate P/N: 61366-1)**[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

## Related Part Information

| General Information                                                                                                                                                   | eCommerce                                                                                                                | Related Part Information                                                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>➤ <a href="#">General Info</a></li><li>➤ <a href="#">Sales Info</a></li><li>➤ <a href="#">Assembly Subcontractors</a></li></ul> | <ul style="list-style-type: none"><li>➤ <a href="#">Pricing</a></li><li>➤ <a href="#">Product Availability</a></li></ul> | <ul style="list-style-type: none"><li>➤ <a href="#">Tooling</a></li></ul> |

## Searchable Features:

|                             |                                                                                                                                                                                          |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Brand:                      | AMP                                                                                                                                                                                      |
| RoHS/ELV Compliance:        | RoHS compliant, ELV compliant                                                                                                                                                            |
| Lead Free Solder Processes: | Wave solder capable to 240°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C |
| Connector Line:             | Automotive MATE-N-LOK                                                                                                                                                                    |
| Contact Diameter (mm [in]): | 1.52 [0.060]                                                                                                                                                                             |

## Other Properties:

|                                   |                           |
|-----------------------------------|---------------------------|
| RoHS/ELV Compliance History:      | Always was RoHS compliant |
| Stock Thickness (mm [in]):        | 0.51 [0.020]              |
| High Current:                     | No                        |
| Contact Termination Area Plating: | Pre-Tin                   |

|                                |                                |
|--------------------------------|--------------------------------|
| Gender:                        | Pin                            |
| Mount:                         | Wire Crimp                     |
| Wire Range (mm [AWG]):         | 0.30-0.90 <sup>2</sup> [22-18] |
| Insulation Diameter (mm [in]): | 1.52-2.79<br>[.060-.110]       |
| Material:                      | Brass                          |
| Packaging Method:              | Strip                          |

[Copyright and Privacy Statement](#)  
Visit [Tyco International Ltd.](#)

[ [Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#) ]