



QUICK DISCONNECTS



















PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

250 REV FLG FAST REC 18 14 BR

FASTON | 250

62048-1

TE Internal Number: 62048-1

Always EU RoHS/ELV Compliant

Mating Tab Width 6.35 mm [.25 in]

Mating Tab Thickness .81 mm [.032 in]

Wire Insulation Diameter 2.29 – 3.3 mm [.09 – .13 in]

Wire Size (AWG) 18 - 14

Wire Size (mm²) .8 – 2

Product Drawings

RECEPTACLE, FASTON, FLAG, REVERSIBLE, .250 SERIES

PDF **English**

CAD Files

Customer View Model

3D STP.ZIP

Customer View Model

2D_DXF.ZIP English

3D PDF

Customer View Model

3D IGS.ZIP English

Catalog Pages/Data Sheets

82004 FASTON Terminals (Insulated And Uninsulated) Catalog - FASTON

Receptacles Section

PDF **English**

Product Specifications

Application Specification

FASTON Reversible Flag Receptacles

PDF **English**

Product Environmental Compliance

TE Material Declaration

MD_62048-1_062920151320_dmtec

PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Insertion Force	Normal
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Insulated	No
	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Paired	No
J	Terminal Angle	Straight
	Connection Capacity	Single
		-
Body Features	Plating Material	Brass, Unplated
Contact Features	Terminal Orientation	Reversible Flag
Termination Features	Crimp Type	F-Crimp
Dimensions	Mating Tab Width	6.35 mm [.25 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter	2.29 – 3.3 mm [.09 – .13 in]
	Wire Size (AWG)	18 – 14
	Wire Size (mm²)	.8 – 2
	Material Thickness	.39 mm [.0157 in]
	Overall Length	18.03 mm [.71 in]
Industry Standards	UL Rating	Listed
	CSA Certified	Yes
Packaging Features	Packaging Method	Reel
	Packaging Quantity	6500
Other	Line	Premier
Product Compliance	Statement of Compliance	

PDF

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

