

MODEL 62

1/4" Diameter

Single Turn

Cermet Trimming

Potentiometer



1

ELECTRICAL

Standard Resistance Range, Ohms	10 to 1Meg
Standard Resistance Tolerance	$\pm 10\%$ (<100 Ohms = $\pm 20\%$)
Input Voltage, Maximum	200 Vdc or rms not to exceed power rating
Slider Current, Maximum	100mA or within rated power, whichever is less
Power Rating, Watts	0.5 at 70°C derating to 0 at 125°C
End Resistance, Maximum	2 Ohms
Actual Electrical Travel, Nominal	220°
Dielectric Strength	600Vrms
Insulation Resistance, Minimum	100 Megohms
Resolution	Essentially infinite
Contact Resistance Variation, Maximum	1% or 1 Ohm, whichever is greater

ENVIRONMENTAL

Seal	85°C Fluorinert® (No Leaks)
Temperature Coefficient, Maximum	$\pm 100\text{ppm}/^\circ\text{C}$
Operating Temperature Range	-55°C to +125°C
Thermal Shock	5 cycles, -55°C to +125°C (1% ΔRT , 1% ΔVR)
Moisture Resistance	Ten 24 hour cycles (1% ΔRT , IR 100 Megohms Min.)
Shock, 6ms Sawtooth	100G's (1% ΔRT , 1% ΔVR)
Vibration	20G's, 10 to 2,000 Hz (1% ΔRT , 1% ΔVR)
High Temperature Exposure	250 hours at 125°C (2% ΔRT , 2% ΔVR)
Rotational Life	200 cycles (2% ΔRT)
Load Life at 0.5 Watts	1,000 hours at 70°C (2% ΔRT)
Resistance to Solder Heat	260°C for 10 sec. (1% ΔRT)

MECHANICAL

Mechanical Stops	Solid
Torque, Starting Maximum	3 oz.-in. (0.021 N-m)
Weight, Nominal	.02 oz. (0.60 grams)

Fluorinert® is a registered trademark of 3M Company.
Specifications subject to change without notice.




1-31

Model 62


TOP ADJUSTMENT (Inch/mm)

Model 62P, 62PF




Note: Model 62P dimensions applicable to all models except as noted.

Model 62B



Model 62M





STANDARD RESISTANCE VALUES, OHMS

10	200	5K	50K	500K
20	500	10K	100K	1Meg
50	1K	20K	200K	
100	2K	25K	250K	


1**PACKAGING**

Standard: Plastic Bags
Capacity = 100 Units

ORDERING INFORMATION**Standard:****CIRCUIT DIAGRAM****NOTES**

Metric equivalents, based on 1 inch = 25.4mm are rounded to the same number of significant figures as in the original English units and are provided for general information only.

Tolerances unless otherwise specified:
Linear = $\pm .01$ inches (.25mm)
Angular = ± 2 degrees



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TT Electronics:

[62MR100LF](#) [62MR10KLF](#) [62MR2KLF](#) [62MR500LF](#) [62MR50KLF](#) [62PR200LF](#) [62PR25KLF](#) [62PR2KLF](#)
[62PR250KLF](#) [62PR200KLF](#) [62PR10LF](#) [62MR1MEGLF](#) [62PR10KLF](#) [62PR1MEGLF](#) [62MR1KLF](#) [62MR500K](#)
[62MR5KLF](#) [62PR20KLF](#) [62MR100KLF](#) [62PR100KLF](#) [62PR50LF](#) [62MR10LF](#) [62MR25KLF](#) [62PR500LF](#)
[62MR200LF](#) [62PR50KLF](#) [62PR1KLF](#) [62MR500KLF](#) [62PR20LF](#) [62PR5KLF](#) [62MR250KLF](#) [62MR20LF](#) [62MR20KLF](#)
[62MR200KLF](#) [62PR100LF](#) [62PR500KLF](#) [62MR50LF](#)