Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



6320UJ Multi-Conductor - Commercial Applications, Addressable Systems - 2 Cond Cabled



For more Information please call

1-800-Belden1



General Description:

NEC Articles:

EU CE Mark:

EU Directive 2011/65/EU (ROHS II):

Fire Alarm Cable, Plenum-FPLP, 2-18 AWG solid bare copper conductors with FEP insulation, Flamarrest®jacket with ripcord

Usage (Overall) Suitable Applications: Addressable Fire Systems, Data Circuits, Monitor/Detection, Control Circuits, Initiating Circuits, Notification Circuits **Physical Characteristics (Overall)** Conductor AWG: # Conductors AWG Stranding Conductor Material 18 Solid BC - Bare Copper **Total Number of Conductors:** 2 Insulation Insulation Material: Insulation Trade Name Insulation Material Thermoplastic Fluoropolymer | .007 **Outer Shield Outer Shield Material: Outer Shield Material** Unshielded **Outer Jacket** Outer Jacket Material: Outer Jacket Trade Name Outer Jacket Material Nom. Wall Thickness (in.) LS PVC - Low Smoke Polyvinyl Chloride | .015 **Outer Jacket Ripcord: Overall Cable** Overall Cabling Lay Length & Direction: Length (in.) Twists (twist/ft) 8.0 Overall Cabling Color Code Chart: Number Color Black Red Overall Nominal Diameter: 0.138 in. **Mechanical Characteristics (Overall) Operating Temperature Range:** 0°C To +75°C 75°C UL Temperature Rating: **Bulk Cable Weight:** 15 lbs/1000 ft. Max. Recommended Pulling Tension: 40 lbs Min. Bend Radius/Minor Axis: 1.400 in. **Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs** NEC/(UL) Specification: FPLP

760

Yes

Yes

Page 1 of 2 01-05-2017

Detailed Specifications & Technical Data





6320UJ Multi-Conductor - Commercial Applications, Addressable Systems - 2 Cond Cabled

	EU Directive 2000/53/EC (ELV):	Yes			
	EU Directive 2002/95/EC (RoHS):	Yes			
	EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005			
	EU Directive 2002/96/EC (WEEE):	Yes			
	EU Directive 2003/11/EC (BFR):	Yes			
	CA Prop 65 (CJ for Wire & Cable):	Yes			
	MII Order #39 (China RoHS):	Yes			
	Other Specification:	California State Fire Marshall			
Fla	Flame Test				
	UL Flame Test:	NFPA 262			
	C(UL) Flame Test:	FT6			
Ple	num/Non-Plenum				
	Plenum (Y/N):	Yes			
	Non-Plenum Number:	5320UJ			
	· ·				

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/ft) .15

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

Max. Operating Voltage - UL:

Voltage 300 V RMS

Max. Recommended Current:

5 Amps per conductor @ 25°C

Notes (Overall)

Notes: Teflon® is a trademark of DuPont.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
6320UJ 0021000	1,000 FT	16.000 LB	RED		2 #18 FEP FLRST

Revision Number: 1 Revision Date: 03-13-2013

© 2017 Belden, Inc

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sales believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its bublication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Page 2 of 2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 6320UJ 0021000