

Part Number: 639948



PTZ, RG-6 #18, #18-2c, CMP, Siamese

## **Product Description**

PTZ (CCTV + Power/Audio) Cable, Plenum-CMP, 1-RG6 18 AWG solid bare copper with foam FEP, 95% bare copper braid, 1-18 AWG stranded bare copper pair with Flamarrest® insulation, Siamese with Flamarrest® jacket

### **Technical Specifications**

#### **Product Overview**

Suitable Applications:	CCTV plus Audio, Pan and Tilt CCTV Control
Physical Characteristics (Overall)	

#### Conductor

AWG	Stranding	Material	Nominal Dia	meter	No. of Conductors	No. of Pairs	No. of Coax
18	Solid	BC - Bare Copper	0.04 in		1	1	1
18	7	BC - Bare Copper	0.047 in				
Conductor Count:		3					
AWG Size:		18					

#### Insulation

Material	Nominal Diameter
FFEP - Foam Fluorinated Ethylene Propylene	0.17 in
PVC - Polyvinyl Chloride	0.062 in

## Color Chart

Number	Color
1	Black and Red

#### Color Chart 2



#### Inner Shield Material

Type	Material	Coverage [%]
Braid	BC - Bare Copper	95 %
	Unshielded	

#### Outer Shield Material



#### **Outer Jacket Material**

Material	Material Trade Name	Nominal Diameter
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.232 in

#### **Construction and Dimensions**

OuterJacket1, Nominal Width:	1 mm
------------------------------	------

## **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Inner Shield DCR
6.4 Ohm/1000ft	6.4 Ohm/1000ft	2.2 Ohm/1000ft

## Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
24 pF/ft	16.1 pF/ft

#### Inductance

Nominal Inductance

## Impedance

Nominal Characteristic Impedance
75 Ohm

## Delay

Max. Delay Skew	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
84 ns/100m	1.21 ns/ft	84 %

## Unbalanced Crosstalk

Typical Unbalanced NEXT %

1 MHz

## Voltage

UL Voltage Rating
300V RMS

## **Temperature Range**

Non-UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

## **Mechanical Characteristics**

Bulk Cable Weight:	60 lbs/1000ft
Max Recommended Pulling Tension:	129 lbs
Min Bend Radius/Minor Axis:	2.5 in

#### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
CPR Euroclass:	Eca
RG Type:	6/U Type

## **Applicable Environmental and Other Programs**

EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Indoor:	Yes	

## Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262

## **Part Number**

Plenum (Y/N):	Yes

	Non-Plenum Number:	539945
--	--------------------	--------

#### Variants

Item #	Color
639948 8771000	Natural
639948 877500	Natural

#### © 2018 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 639948 8771000 639948 877500