

For more Information
please call

1-800-Belden1



General Description:

Surveillance & CCTV Cable, RG59, Plenum-CMP, 20 AWG solid bare copper, foamed FEP core, 95% bare copper braid, Flamarrest® jacket

Usage (Overall)

Suitable Applications: CCTV

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	Solid	BC - Bare Copper	.032

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)
Teflon®	FFEP - Foam Fluorinated Ethylene Propylene	.135

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 0.192 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +75°C
UL Temperature Rating:	75°C
Bulk Cable Weight:	30 lbs/1000 ft.
Max. Recommended Pulling Tension:	52 lbs.
Min. Bend Radius/Minor Axis:	1.750 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
NEC Articles:	800
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (RoHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

643948 Coax - CCTV Applications

RG Type: 59/U

Series Type: Series 59

Flame Test

UL Flame Test: NFPA 262

C(UL) Flame Test: FT6

Plenum/Non-Plenum

Plenum (Y/N): Yes

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

75

Nom. Inductance:

Inductance (µH/ft)

.097

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

16.1

Nominal Velocity of Propagation:

VP (%)

84

Nominal Delay:

Delay (ns/ft)

1.21

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

10.0

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

3.300

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	0.29
3	0.58
5	0.70
8	0.87
10	1.05
50	1.80
100	2.7
200	3.9
400	5.9
700	8.5
900	10.0
1000	10.7

Max. Operating Voltage - UL:

Voltage

300 V RMS

Notes (Overall)

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
643948 010U1000	1,000 FT	30.000 LB	BLACK		#20 FFEP BRD FLRST
643948 010U500	500 FT	16.000 LB	BLACK		#20 FFEP BRD FLRST
643948 010I1000	1,000 FT	32.000 LB	BLACK	C	#20 FFEP BRD FLRST
643948 877U1000	1,000 FT	28.000 LB	NATURAL		#20 FFEP BRD FLRST
643948 877U500	500 FT	15.000 LB	NATURAL		#20 FFEP BRD FLRST
643948 877I1000	1,000 FT	29.000 LB	NATURAL	C	#20 FFEP BRD FLRST

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 08-12-2013

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

[643948 010U1000](#) [643948 010U500](#) [643948 0101000](#) [643948 877U1000](#) [643948 877U500](#) [643948 8771000](#)