


wakefield-vette


Standard P/N	Height Above PC Board "A" in. (mm)	Maximum Footprint in. (mm)	Thermal Performance at Typical Load		Weight lbs (grams)
			Natural Convection	Forced Convection	
657-10ABEP	1.000 (25.4)	1.650 (41.9) x 1.000 (25.4)	41°C @ 6W	3.7°C/W @ 200 LFM	0.0515 (23.36)
657-15ABEP	1.500 (38.1)	1.650 (41.9) x 1.000 (25.4)	38°C @ 6W	3.3°C/W @ 200 LFM	0.0760 (34.60)
657-20ABEP	2.000 (50.8)	1.650 (41.9) x 1.000 (25.4)	32°C @ 6W	2.9°C/W @ 200 LFM	0.1030 (47.00)
657-25ABEP	2.500 (63.5)	1.650 (41.9) x 1.000 (25.4)	25°C @ 6W	2.7°C/W @ 200 LFM	0.1250 (57.00)

MECHANICAL DIMENSIONS

657 SERIES
(EXTRUSION PROFILE 6533)




Dimensions: in. (mm)



NATURAL AND FORCED CONVECTION CHARACTERISTICS

AIR VELOCITY (FPM)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Wakefield-Vette:](#)

[657-15ABPE](#) [657-20ABPEN](#) [657-10ABEPN](#) [657-20ABEP](#) [657-25ABEP](#) [657-25ABEPN](#) [657-20ABEPSC](#) [657-25ABPE](#) [657-20ABPE](#) [657-10ABPE](#)