

LOC	DIST	REVISIONS					
CE	16	F	LTR	DESCRIPTION	DATE	DWN	APVD
			A	DRAWN	12JAN06	EH	AP

THREADED INSERT #M6 X 1-6H THREAD
MATERIAL BRASS

⚠ MATERIAL: THERMOPLASTIC ELASTOMER
ARNITEL PL460S
FLAMABILITY RATING: UL94V-0
COLOR: BLACK

2. BULK PACKAGE 25 PCS.

3. RETENTION FORCE 1/2 LB MIN.

⚠ 4 USE HANDLE PART NUMBER 503967-5 WITH
DUST COVER ASSEMBLY.

⚠ 5 MATERIAL: THERMOPLASTIC ELASTOMER
ARNITEL PL460S
FLAMABILITY RATING: UL94V-0
COLOR: RED

⚠ 6 MATERIAL: THERMOPLASTIC ELASTOMER
ARNITEL PL460S
FLAMABILITY RATING: UL94V-0
COLOR: GREEN

⚠ 7 MATERIAL: THERMOPLASTIC ELASTOMER
ARNITEL PL460S
FLAMABILITY RATING: UL94V-0
COLOR: BLUE

17
MIN AT CLOSED END

SCALE 4:1

17.54
MAX AT OPEN END

SECTION B-B

SECTION C-C

BLUE	⚠ 7	6588897-7
GREEN	⚠ 6	6588897-5
RED	⚠ 5	6588897-3
BLACK	⚠ 4	6588897-1
COLOR	MATERIAL	PART NO.

TYP. DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION IT IS SUBJECT TO THE FOLLOWING RESTRICTIONS: 1. IT IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM TYCO ELECTRONICS CORPORATION. 2. IT IS TO BE USED ONLY FOR THE PURPOSES SPECIFIED IN THE DRAWING. 3. IT IS TO BE KEPT IN THE ORIGINAL FORM AND NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM TYCO ELECTRONICS CORPORATION.		DWN E. HALEY 12JAN06	AMP Incorporated Harrisburg, PA 17105-3608	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±. 1 PLC ±0.2 2 PLC ±0.13 3 PLC ±. 4 PLC ±. ANGLES 2°	CHK A PLOTS 12JAN06	NAME DUST COVER, 1X4 VERTICAL, LIGHTRAY MPX	
		APVD A PLOTS 12JAN06	PRODUCT SPEC	
MATERIAL -	FINISH -	APPLICATION SPEC	SIZE A 00779 ©=6588897	
		WEIGHT -	RESTRICTED TO -	
CUSTOMER DRAWING			SCALE 3:1	SHEET 1 OF 1 REV A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6588897-5](#)