

1				2				3				4				5															
2.20 7.0 0.25 2.54±0.30 0.50 1.27 0.56 6.70 3.1 2.54±0.05 1.27±0.05 TYP. 2.54±0.05 Ø0.80±0.10 1 End B±0.30 C±0.20 A±0.10 1.27±0.05 1.50 4.10 5.0 2.54 1 End																TECHNICAL CHARACTERISTICS MATERIAL HOUSING MATERIAL: GLASS FILLED POLYESTER COLOR: RED MAX TEMP.: 260°C 10s CONTACT MATERIAL: PHOSPHOR BRONZE CONTACT TYPE: STAMPED CONTACT PLATING: MATT TIN OVER NICKEL QUALITY CLASS: 25 MATING CYCLES PITCH: 2.54 MM PER ROW ENVIRONNEMENTAL OPERATING TEMPERATURE: -40°C UP TO 105°C FLAMABILITY RATING: UL94-V0 COMPLIANCE: LEAD FREE AND ROHS ELECTRICAL CURRENT RATING: 1.5 A PER PIN (PCB PIN) WORKING VOLTAGE: 100 VAC INSULATION RESISTANCE: >1000 MOHM DIELECTRIC WITHSTANDING VOLT.: 500 VAC/MN CONTACT RESISTANCE: 10 mOHM MAX STANDARD CERTIFIED: E323964 SOLDERING JEDEC LEAD FREE WAVE SOLDERING DIMENSION: DIM.A= 1.27 x No. of Spaces DIM.B= DIM.A + 3.3 DIM.C= DIM.A + 2.1 AVAILABLE xx : 4 TO 26 CIRCUITS PACKAGING: x = 2 TUBE x = 7 TAPE & REEL															
RoHS Compliant								PROJECTION:				GENERAL TOLERANCE				WÜRTH ELEKTRONIK															
G								UNIT: MM				DESCRIPTION: MM MALE CONNECTOR WITHOUT LATCH AND POLARIZATION				SIZE															
F																															
E																															
D																															
C				APPROVAL: GMo				SCALE:				WERI PART NO: 690 357 10x x7x				A4															
B	06-FEB-17	CERTIFIED	AK					SHEET: 1/2																							
A	03-NOV-06	PDF	JP					DRAW: EAGER																							
REV	DATE	FILE	BY																												

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Würth Electronics:](#)

[690357100472](#) [690357100872](#) [690357102072](#) [690357101072](#) [690357101272](#) [690357100672](#)