





1		2		3		4		5																																																																																											
						<table><tr><th colspan="6">Pitch : 5.08mm(0.200inch)</th></tr><tr><th>Poles</th><th>A(mm)</th><th>A(inch)</th><th>Poles</th><th>A(mm)</th><th>A(inch)</th></tr><tr><td>2</td><td>10.16</td><td>0.400</td><td>15</td><td>76.20</td><td>3.000</td></tr><tr><td>3</td><td>15.24</td><td>0.600</td><td>16</td><td>81.28</td><td>3.200</td></tr><tr><td>4</td><td>20.32</td><td>0.800</td><td>17</td><td>86.36</td><td>3.400</td></tr><tr><td>5</td><td>25.40</td><td>1.000</td><td>18</td><td>91.44</td><td>3.600</td></tr><tr><td>6</td><td>30.48</td><td>1.200</td><td>19</td><td>96.52</td><td>3.800</td></tr><tr><td>7</td><td>35.56</td><td>1.400</td><td>20</td><td>101.60</td><td>4.000</td></tr><tr><td>8</td><td>40.64</td><td>1.600</td><td>21</td><td>106.68</td><td>4.200</td></tr><tr><td>9</td><td>45.72</td><td>1.800</td><td>22</td><td>111.76</td><td>4.400</td></tr><tr><td>10</td><td>50.80</td><td>2.000</td><td>23</td><td>116.84</td><td>4.600</td></tr><tr><td>11</td><td>55.88</td><td>2.200</td><td>24</td><td>121.92</td><td>4.800</td></tr><tr><td>12</td><td>60.96</td><td>2.400</td><td></td><td></td><td></td></tr><tr><td>13</td><td>66.04</td><td>2.600</td><td></td><td></td><td></td></tr><tr><td>14</td><td>71.12</td><td>2.800</td><td></td><td></td><td></td></tr></table>				Pitch : 5.08mm(0.200inch)						Poles	A(mm)	A(inch)	Poles	A(mm)	A(inch)	2	10.16	0.400	15	76.20	3.000	3	15.24	0.600	16	81.28	3.200	4	20.32	0.800	17	86.36	3.400	5	25.40	1.000	18	91.44	3.600	6	30.48	1.200	19	96.52	3.800	7	35.56	1.400	20	101.60	4.000	8	40.64	1.600	21	106.68	4.200	9	45.72	1.800	22	111.76	4.400	10	50.80	2.000	23	116.84	4.600	11	55.88	2.200	24	121.92	4.800	12	60.96	2.400				13	66.04	2.600				14	71.12	2.800			
Pitch : 5.08mm(0.200inch)																																																																																																			
Poles	A(mm)	A(inch)	Poles	A(mm)	A(inch)																																																																																														
2	10.16	0.400	15	76.20	3.000																																																																																														
3	15.24	0.600	16	81.28	3.200																																																																																														
4	20.32	0.800	17	86.36	3.400																																																																																														
5	25.40	1.000	18	91.44	3.600																																																																																														
6	30.48	1.200	19	96.52	3.800																																																																																														
7	35.56	1.400	20	101.60	4.000																																																																																														
8	40.64	1.600	21	106.68	4.200																																																																																														
9	45.72	1.800	22	111.76	4.400																																																																																														
10	50.80	2.000	23	116.84	4.600																																																																																														
11	55.88	2.200	24	121.92	4.800																																																																																														
12	60.96	2.400																																																																																																	
13	66.04	2.600																																																																																																	
14	71.12	2.800																																																																																																	
TECHNICAL CHARACTERISTICS MATERIAL INSULATOR: PA 66 FLAMABILITY RATING: UL94-V0 COLOR: GREEN METAL HOUSING: PhBz TIN PLATED TERMINAL SCREW: STEEL ZINC PLATING TERMINAL SCREW SLOT TYPE: "+" WIRE GUARD: STEEL ZINC PLATING FLANGES SCREW: STEEL M2.6 ENVIRONMENTAL OPERATING TEMPERATURE: -40 UP TO 105°C COMPLIANCE: LEAD FREE AND ROHS ELECTRICAL CURRENT RATING: 16A WORKING VOLTAGE: 300VAC WITHSTANDING VOLTAGE: 2KV CONTACT RESISTANCE: 20 mOhm max STANDARD ULus CERTIFIED E315414 / Model number 69137350 MECHANICAL SOLID WIRE: 24-12 AWG / 0.02-3.3MM² STRANDED WIRE: 24-12 AWG / 0.02-3.3MM² TORQUE: 4.5Lb-In / 0.5Nm WIRE STRIPE LENGTH: 10MM PITCH: 5.08MM PACKAGING: BOX SERIE 373B																																																																																																			
<table><tr><td colspan="4">RoHS Compliant</td></tr><tr><td>G</td><td></td><td></td><td></td></tr><tr><td>F</td><td></td><td></td><td></td></tr><tr><td>E</td><td></td><td></td><td></td></tr><tr><td>D</td><td></td><td></td><td></td></tr><tr><td>C</td><td></td><td></td><td></td></tr><tr><td>B</td><td></td><td></td><td></td></tr><tr><td>A</td><td>20-JUN-12</td><td>PDF</td><td>GG</td></tr><tr><td>REV</td><td>DATE</td><td>FILE</td><td>BY</td></tr></table>						RoHS Compliant				G				F				E				D				C				B				A	20-JUN-12	PDF	GG	REV	DATE	FILE	BY	PROJECTION: 		GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15 																																																							
RoHS Compliant																																																																																																			
G																																																																																																			
F																																																																																																			
E																																																																																																			
D																																																																																																			
C																																																																																																			
B																																																																																																			
A	20-JUN-12	PDF	GG																																																																																																
REV	DATE	FILE	BY																																																																																																
APPROVAL: RJ				UNIT: MM SCALE: SHEET: 1/1 DRAW: MARVIN																																																																																															
				DESCRIPTION: SERIE 373B - 5,08mm Vertical Cable Entry with Stamping Clamp - 3,3 mm² Wire WERI PART NO: 691 373 500 0xx B																																																																																															
				SIZE A4																																																																																															