



SAFETY DATA SHEET
COLD GALVANISING SPRAY

Page: 1

Compilation date: 22/12/2011

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: COLD GALVANISING SPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Metal galvanising spray

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House

Swillington

Leeds

West Yorkshire

LS26 8BS

ENGLAND

Tel: +44 (0) 113 232 2700

Fax: +44 (0) 113 232 2740

Email: customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; N: R50/53

Most important adverse effects: Extremely flammable. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Extremely flammable.

Dangerous for the environment.



Risk phrases: R12: Extremely flammable.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S16: Keep away from sources of ignition - No smoking.

[cont...]

SAFETY DATA SHEET

COLD GALVANISING SPRAY

Page: 2

S23: Do not breathe spray.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ZINC

EINECS	CAS	CHIP Classification	CLP Classification	Percent
231-175-3	7440-66-6	N: R50/53	-	50-70%

DIMETHYL ETHER AEROSOL PROPELLANT

204-065-8	115-10-6	F+: R12	-	10-30%
-----------	----------	---------	---	--------

HYDROGENATED HYDROCARBON (<0.1% BENZENE)

265-150-3	64742-48-9	-: R10; Xn: R65; -: R66	-	1-10%
-----------	------------	-------------------------	---	-------

1-METHOXY-2-PROPANOL

203-539-1	107-98-2	-: R10; -: R67	-	1-10%
-----------	----------	----------------	---	-------

HYDROTREATED NAPHTHENIC DISTILLATE

265-097-6	64741-96-4	-	-	1-10%
-----------	------------	---	---	-------

XYLENE

215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	-	1-10%
-----------	-----------	-----------------------------	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

SAFETY DATA SHEET

COLD GALVANISING SPRAY

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Do not use water. Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. Forms explosive air-vapour mixture. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden.

[cont...]

SAFETY DATA SHEET

COLD GALVANISING SPRAY

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ZINC

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	3mg/m ³	-

DIMETHYL ETHER AEROSOL PROPELLANT

UK	400ppm 766mg/m ³	500ppm 958mg/m ³	-	-
----	-----------------------------	-----------------------------	---	---

HYDROGENATED HYDROCARBON (<0.1% BENZENE)

UK	1000mg/m ³	-	-	-
----	-----------------------	---	---	---

1-METHOXY-2-PROPANOL

UK	375 mg/m ³	560 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

HYDROTREATED NAPHTHENIC DISTILLATE

UK	5mg/m ³	10mg/m ³	-	-
----	--------------------	---------------------	---	---

XYLENE

UK	220 mg/m ³	441 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not normally required for normal use in well ventilated areas. Respiratory protection should be used in enclosed spaces, with poor ventilation, for extended repeated use, or if workplace exposure limits may be exceeded. A dust mask with P2 particle filter is recommended

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

[cont...]

SAFETY DATA SHEET
COLD GALVANISING SPRAY

Page: 5

9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: Dark grey
Odour: Characteristic odour
Evaporation rate: Fast
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Not miscible
Viscosity: Non-viscous
Boiling point/range°C: -25
Flammability limits %: lower: 3.4
Flash point°C: < -40
Vapour pressure: 490
Melting point/range°C: < 0
upper: 18
Autoflammability°C: > 300
Relative density: 1.4

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: Not applicable.

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.

[cont...]

SAFETY DATA SHEET

COLD GALVANISING SPRAY

Page: 6

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Highly volatile. Heavier than air.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Very toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

[cont...]

SAFETY DATA SHEET
COLD GALVANISING SPRAY

Page: 7

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Safety data sheet prepared in accordance with Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC relating to aerosol dispensers

Phrases used in s.2 and 3: R10: Flammable.

R12: Extremely flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.