



SITOP PSU300S 40A STABILIZED POWER SUPPLY
INPUT: 400-500 V 3AC OUTPUT: 24 V DC/40 A

Technical specifications

Product	SITOP PSU300S
Power supply, type	24 V/40 A
Input	
Input	3-phase AC
Supply voltage / at AC / nominal value min.	400 V
Supply voltage / at AC / nominal value max.	500 V
Supply voltage	
• at AC	340 ... 550 V
Wide-range input	Yes
Mains buffering at Iout rated, min.	6 ms
Mains buffering	at Vin = 400 V
Rated line frequency	50 / 60 Hz
Rated line range	47 ... 63 Hz
Input current / at nominal level of the input voltage 400 V	2 A
Input current / at nominal level of the input voltage 500 V	1.7 A
Switch-on current limiting (+25 °C), max.	60 A
I ² t, max.	3.4 A ² ·s
Built-in incoming fuse	none

Protection in the mains power input (IEC 898)		Required: 3-pole connected miniature circuit breaker 10 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)
Output		
Output	Controlled, isolated DC voltage	
Rated voltage Vout DC	24 V	
Total tolerance, static \pm	3 %	
Static mains compensation, approx.	1 %	
Static load balancing, approx.	2 %	
Residual ripple peak-peak, max.	150 mV	
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV	
Adjustment range	24 ... 28 V	
Product feature / output voltage adjustable	Yes	
Output voltage setting	via potentiometer	
• Note	max. 960 W	
Status display	Green LED for 24 V OK	
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"	
On/off behavior	No overshoot of Vout (soft start)	
Startup delay, max.	1.5 s	
Voltage rise, typ.	15 ms	
Voltage increase time / of the output voltage / maximum	500 ms	
Rated current value Iout rated	40 A	
Current range	0 ... 40 A	
• Note	48 A up to +45°C; +60 ... +70 °C: Derating 2.5%/K	
delivered active power / typ.	960 W	
short-term overload current / at short-circuit during run-up / typical	65 A	
Duration of overloading ability for excess current / on short-circuiting during the start-up	120 ms	
short-term overload current / at short-circuit during operation / typical	65 A	
Duration of overloading ability for excess current / on short-circuiting during the operational phase	120 ms	
Parallel switching for enhanced performance	Yes	
Numbers of parallel switchable units for enhanced performance	2	
Efficiency		
Efficiency at Vout rated, Iout rated, approx.	91.5 %	
Power loss at Vout rated, Iout rated, approx.	89 W	
Closed-loop control		
Dynamic mains compensation (Vin rated ± 15 %), max.	3 %	
Dynamic load smoothing (Iout: 50/100/50 %), Uout \pm typ.	1.5 %	
Load step setting time 50 to 100%, typ.	1 ms	
Load step setting time 100 to 50%, typ.	1 ms	

Setting time / maximum	10 ms
Protection and monitoring	
Output overvoltage protection	protection against overvoltage in case of internal fault Vout < 35 V
Current limitation, typ.	50 A
Characteristic feature of the output / short-circuit protected	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Enduring short circuit current / Effective level / maximum	14 A
Enduring short circuit current / Effective level / typical	
• Note	overload capability 150 % Iout rated up to 5 s/min
Safety	
Primary/secondary isolation	Yes
Potential separation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
Protection class	Class I
CE mark	Yes
UL/CSA approval	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
Explosion protection	ATEX (EX) II 3G Ex nA nC IIC T3; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T3
FM approval	-
CB approval	Yes
Marine approval	GL, ABS
Degree of protection (EN 60529)	IP20
EMC	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2
Operating data	
Ambient temperature / in operation	0 ... 70 °C
• Note	with natural convection
Ambient temperature / on transport	-40 ... +85 °C
Ambient temperature / in storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation
Mechanics	
Connection technology	screw-type terminals
Connections / Supply input	L1, L2, L3, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded
Connections / Output	+, -: 2 screw terminals each for 0.5 ... 10 mm ²
Connections / Auxiliary	13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm ²
Width / of the housing	150 mm

Height / of the housing	145 mm
Depth / of the housing	150 mm
Installation width	150 mm
Mounting height	225 mm
Weight, approx.	3.7 kg
Product feature / of the housing / housing for side-by-side mounting	Yes
Mounting type / wall mounting	No
Type of mounting / standard rail mounting	Yes
Mounting type / S7 rail mounting	No
Installation	Snaps onto DIN rail EN 60715 35x15
Electrical accessories	Buffer module
Mechanical accessories	Device identification label 20 mm x 7 mm, pastel-turquoise 3RT1900-1SB20
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

letzte Änderung:

Aug 8, 2014