

SITOP DC UPS MODULE 6A WITHOUT INTERFACE  
 SITOP DC UPS MODULE 24 V/6 A UNINTERRUPTIBLE POWER  
 SUPPLY WITHOUT INTERFACE INPUT: 24 V DC/6.85 A OUTPUT:  
 24 V DC/6 A



Input	
Supply voltage at DC Rated value	24 V
Voltage curve at input	DC
input voltage range	22 ... 29 V DC
Mains buffering	
Type of energy storage	with batteries
Charging current	
• 1	0.2 A
• 2	0.4 A
Output	
Output voltage	
• in normal operation at DC Rated value	24 V
• in buffering mode at DC Rated value	24 V
Formula for output voltage	$V_{in} - \text{approx. } 0.5 \text{ V}$
ON-delay time typical	1 s
Voltage increase time of the output voltage typical	60 ms
Output current Rated value	6 A
Property of the output Short-circuit proof	Yes

Active power supplied typical	144 W
<b>Efficiency</b>	
Efficiency in percent	
<ul style="list-style-type: none"> <li>at rated output current at rated output current typical</li> </ul>	95 %
<ul style="list-style-type: none"> <li>in case of accumulator operation typical</li> </ul>	94.5 %
Active power loss	
<ul style="list-style-type: none"> <li>at rated output current at rated output current typical</li> </ul>	7 W
<ul style="list-style-type: none"> <li>in case of accumulator operation typical</li> </ul>	8 W
<b>Protection and monitoring</b>	
Product function	
<ul style="list-style-type: none"> <li>reverse polarity protection against energy storage unit polarity reversal</li> </ul>	Yes
<ul style="list-style-type: none"> <li>reverse polarity protection against input voltage polarity reversal</li> </ul>	Yes
<b>Signaling</b>	
Display version	
<ul style="list-style-type: none"> <li>for normal operation</li> </ul>	Normal operation: LED green (OK), floating changeover contact "Bat/OK" to setting "OK" ("OK" means: Voltage of the supplying power supply unit is greater than cut-in threshold set at the DC UPS module); Lack of buffer standby: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Battery replacement required: LED red (alarm) flashing with approx. 0.25 Hz, floating changeover contact "Alarm/Bat" switching with approx. 0.25 Hz; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed; Permissible contact current capacity: DC 60 V/1 A or AC 30 V /1 A
<ul style="list-style-type: none"> <li>in buffering mode</li> </ul>	Buffered mode: LED yellow (Bat), floating changeover contact "OK/Bat" to setting "Bat"; Prewarning battery voltage < 20.4 VDC: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed
<b>Interface</b>	
Product component PC interface	No
Design of the interface	without
<b>Safety</b>	
Galvanic isolation between entrance and outlet	No
Operating resource protection class	Class III
Certificate of suitability	
<ul style="list-style-type: none"> <li>CE marking</li> </ul>	Yes
<ul style="list-style-type: none"> <li>UL approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>as approval for USA</li> </ul>	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259

<ul style="list-style-type: none"> <li>• relating to ATEX</li> <li>• C-Tick</li> </ul>	-
Shipbuilding approval	-
Protection class IP	IP20

## EMC

Standard	
<ul style="list-style-type: none"> <li>• for emitted interference</li> <li>• for interference immunity</li> </ul>	EN 55022 Class B EN 61000-6-2

## Operating data

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> <li>• during transport</li> <li>• during storage</li> </ul>	-25 ... +60 °C -40 ... +85 °C -40 ... +85 °C
Environmental category acc. to IEC 60721	Climate class 3K3, no condensation

## Mechanics

Type of electrical connection	screw-type terminals
<ul style="list-style-type: none"> <li>• at input</li> <li>• at output</li> <li>• for battery module</li> <li>• for control circuit and status message</li> </ul>	24 V DC: 2 screw terminals for 1 ... 4 mm²/17 ... 11 AWG 24 V DC: 4 screw terminals for 1 ... 4 mm²/17 ... 11 AWG 24 V DC: 2 screw terminals for 1 ... 4 mm²/17 ... 11 AWG 10 screw terminals for 0.5 ... 2.5 mm²/20 ... 13 AWG
Width of the enclosure	50 mm
Height of the enclosure	125 mm
Depth of the enclosure	125 mm
Required spacing	
<ul style="list-style-type: none"> <li>• top</li> <li>• bottom</li> <li>• left</li> <li>• right</li> </ul>	50 mm 50 mm 0 mm 0 mm
Net weight	0.4 kg
Product property of the enclosure housing for side-by-side mounting	Yes
Mounting type	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Battery module
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)