



SITOP CNX8600 4X 5A EXTENSION MODULE FOR PSU8600  
OUTPUT: 24 V/4X 5 A DC

### Technical specifications

Product	SITOP CNX8600
Power supply, type	4x 5 A
<b>Output</b>	
Output	Controlled, isolated DC voltage
Number of outputs	4
Rated voltage Vout DC	24 V
Output voltage at output 1 for DC Rated value	24 V
Output voltage at output 2 for DC Rated value	24 V
Output voltage at output 3 for DC Rated value	24 V
Output voltage at output 4 for DC Rated value	24 V
Total tolerance, static $\pm$	3 %
Static mains compensation, approx.	0.2 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	100 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	200 mV
Adjustment range	11 ... 28 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer; Derating > 24 V: 4%/V; max. 120 W per output, max. 960 W overall system
Status display	3-color LED for operating state module; 3-color LED per output for operating state output
Signaling	Relay contact (changeover contact, contact current capacity DC 60 V/0.3 A) for "Operating state OK" at power supply unit PSU8600
On/off behavior	No overshoot of Vout (soft start)

Startup delay, max.	1.5 s; Without on-delay of the outputs
connection of outputs operating	Simultaneous connecting-in of all outputs after device booting or delay time of 25 ms, 100 ms or "load-optimized" for sequential cutting-in of the outputs via DIP switches at power supply unit PSU8600 can be set
Voltage increase time of the output voltage maximum	500 ms
Rated current value $I_{out}$ rated	20 A
Output current per output	5 A
Output current at output 1 Rated value	5 A
Output current at output 2 Rated value	5 A
Output current at output 3 Rated value	5 A
Output current at output 4 Rated value	5 A
Current range	0 ... 20 A
• Note	No increase in the maximum output power of the overall system SITOP PSU8600 via the expansion module SITOP CNX8600 possible
Active power supplied typical	480 W
Product property parallel switching of outputs	No
Parallel switching for enhanced performance	No
<b>Efficiency</b>	
Efficiency at $V_{out}$ rated, $I_{out}$ rated, approx.	97 %
Power loss at $V_{out}$ rated, $I_{out}$ rated, approx.	15 W
<b>Closed-loop control</b>	
Dynamic mains compensation ( $V_{in}$ rated $\pm 15\%$ ), max.	0.1 %
Dynamic load smoothing ( $I_{out}$ : 50/100/50 %), $U_{out} \pm$ typ.	0.4 %
Setting time maximum	10 ms
<b>Protection and monitoring</b>	
Output overvoltage protection	< 35 V
Property of the output Short-circuit proof	Yes
Short-circuit protection	electronic overload cut-off
adjustable response value current of current-dependent overload trip	0.2 ... 5 A
type of threshold value setting	via potentiometer
characteristics of electronic overload switch-off	$I_a > 1.0 \dots < 1.5 \times I_a$ threshold permissible for 5 s; $I_a$ limit ( $= 1.5 \times I_a$ threshold) permissible for 200 ms
Reset	Via sensor per output
Remote reset	Non-electrically isolated 24 V input (signal level "high" at $> 15$ V) at power supply unit PSU8600
Overload/short-circuit indicator	3-color LED for operating state module; 3-color LED per output for operating state output
<b>Interface</b>	

Specification interface	Ethernet/PROFINET via power supply unit PSU8600
<b>Safety</b>	
Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
Protection class	Class I
CE mark	Yes
UL/CSA approval	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
Explosion protection	-
Certificate of suitability IECEx	Yes
Certificate of suitability NEC Class 2	No
FM approval	-
CB approval	Yes
Approvals	No
Marine approval	-
Degree of protection (EN 60529)	IP20
<b>EMC</b>	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
<b>Operating data</b>	
Ambient temperature during operation	-25 ... +60 °C
• Note	with natural convection
Ambient temperature during transport	-40 ... +85 °C
Ambient temperature during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation
<b>Mechanics</b>	
Connection technology	Plug-in terminals with screwed connection
Connections Output	1, 2, 3, 4: Two plug-in terminals (1, 2 and 3, 4) with 2 screwed connections each for 0.2 ... 2.5 mm <sup>2</sup> ; Ground: Plug-in terminal with 3 screwed connections for 0.2 ... 2.5 mm <sup>2</sup>
Product function removable terminal at output	Yes
Suitability for interaction modular system	Yes
Type of connection to system components	Via integrated connector
Width of the enclosure	60 mm
Height of the enclosure	125 mm
Depth of the enclosure	150 mm
Required spacing top	50 mm
Required spacing bottom	50 mm
Required spacing left	0 mm
Required spacing right	0 mm
Weight, approx.	1.15 kg

Product property of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x15
Mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)