

Product type designation

MM992-4CU

SCALANCE X ACCESSORIES; MEDIA MODULE MM992-4CU; 4 X 1000MBIT/S RJ45-PORTS, ELECTRICAL; WITHOUT SLEEVE



Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	4
Number of electrical connections • for network components or terminal equipment / maximum	4
Number of 10/100/1000 Mbit/s RJ45 ports	4
Type of electrical connection • for network components or terminal equipment	RJ45

Permitted ambient conditions

Ambient temperature • during operation • during storage • during transport	0 ... 60 °C -40 ... +85 °C -40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Design	Media module
Width	120.3 mm
Height	22.3 mm
Depth	275.5 mm
Net weight	0.3 kg
Mounting type	latched
• Installation in media module slot	Yes

Standards, specifications, approvals

Standard	
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-7
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Certificate of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
• CE marking	Yes
• C-Tick	Yes
• KC approval	Yes
• E1 approval	No

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 07/08/2016