## Sizes on Page 2

# 3M™ Moisture Barrier Bag Dri-Shield 2000

## Moisture Barrier Bag ~ Aluminized

The 3M Dri-Shield 2000 Moisture Barrier Bag is designed for dry packaging of electronic devices. Dri-Shield 2000 bags are made from multiple layers of metallized polyester and dissipative polyethylene. Bags protect SMD's from moisture and static damage. Flexible structure is easy to vacuum seal. Coded for QC traceability. These bags are tested to meet or exceed certain electrical and physical requirements of ANSI/ESD S541, EIA 625, and to be ANSI/ESD S20.20 program compliant.

## **Specifications**

**Physical Properties:** Typical Values Test Method\* **MVTR** <.02 a/100 sa.in./24 hrs **ASTM F 1249** Puncture Resistance > 20 lbs MIL-STD-3010 2065 Thickness 3.6 mils MIL-STD-3010 1003 Tensile Strength 8700 PSI ASTM D882 Seal Strength ASTM D882 >12 lbs

**Heat Sealing Conditions:** 

300°F - 400°F Temperature 0.6 - 4.5 seconds Time 30 - 70 PSI Pressure

### **Electrical Properties:**

Surface Resistivity / Resistance ASTM D257 or ANSI/ESD STM11.11 <10<sup>12</sup> ohms/square <10<sup>11</sup> ohms Interior <10<sup>12</sup> ohms/square  $<10^{11}$  ohms Exterior

Metal 100 ohms < 20 volts

Static Shielding Static Shielding < 10 nJ

**EMI** Attenuation 45 dB

< 0.03 seconds Static Decay

Silicone or Amine Content Not detected FTIR


## **Material Structure**

Multiple layers of metallized polvester provide puncture resistance and moisture barrier for this economical dry package. This highly reliable material meets or exceeds MVTR and EMI/RFI/Static requirements for static safe, STATIC DISSIPATIVE moisture barrier packaging.



Moisture Barrier Bag with Humidity Indicator Card and Desiccant





### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty: Limited Remedy: Limited Liability.

This product will be free from defects in material and manufacture for one year from the date of purchase. 3M MAKES NO OTHER WAR-RANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WAR-RANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

\*This product is not on the Qualified Product Listing under the Defense Standardization Program.

of their respective owners.

3M is a trademark of 3M Company.

All other trademarks herein are the property

## See 3M Data Sheets for these related items:

Humidity Indicator Cards (HIC's)

Desiccant

Vacuum Sealers

#### C T D A T S H EET

# Dri-Shield 2000 Moisture Barrier Bag ALUMINIZED

PRODUCT MOISTURE BARRIER BAG, ALUMINIZED ITEM NUMBER 700(W")(L")

FIA 541

ANSI/ESD STM11.31

MIL-STD-3010 4046

DATASHEET 1102-A 98-0799-1075-2 3M Electronic Solutions Division 6801 River Place Blvd Austin, TX 78726-9000 US and Canada: 866-722-3736 Fax: 866-722-3735

Intl: 919-718-0000: Fax: 919-774-8174

email: 3Mstaticinfo@mmm.com; www.3Mstatic.com © 3M 2011. All rights reserved




# 3M™ Moisture Barrier Bag Dri-Shield 2000

## Moisture Barrier Bag ~ Aluminized

W"x L"	P/N	W"x L" P/N	W"x L" P/N
V V V L	1 /11	VV A L 1 /1V	VV A L 1 /1V
3 x 5	70035	8 x 10 700810	14 x 30 7001430
4 x 6	70046	8 x 12 700812	15 x 18 7001518
4 x 24	700424	10 x 12 7001012	16 x 18 7001618
5 x 30	700530	10 x 20 7001020	17 x 19 7001719
6 x 8	70068	10 x 24 7001024	18 x 18 7001818
6 x 10	700610	10 x 30 7001030	18 x 24 7001824
6 x 24	700624	12 x 16 7001216	
6 x 30	700630	12 x 18 7001218	

- All standard sizes in-stock/same day shipment.
- Width is measured from inside seam to inside seam.
- Length is measured from the top edge to the bottom fold.
- Opening is in the "width" dimension.
- Custom bag sizes, custom printing, and custom hot stamping are available.
- Most sizes are packed 100 per case. Small sizes are packed 1000 or 500 per case.

## 3M Dri-Shield 2000



## **How Moisture Barrier Bags Work**

Moisture barrier bags work by enclosing a device with a metal or plastic shield(s) that has a high resistance to moisture vapor permeation. Dry devices are placed inside this shield, and the moisture-laden air is evacuated. Desiccant filled pouches scavenge the remaining moisture from the bag's interior. Moisture that penetrates the bag is also entrapped by the desiccant. Humidity indicating cards report the effectiveness of the package upon device use. A label on the bag indicates the amount of exposure time devices are allowed prior to use, and the drying (re-baking) time and temperature if the exposure time is exceeded.

As the barrier property improves, the Moisture Vapor Transmission Rate (MVTR) decreases. Bags with lower MVTR provide better barrier. Aluminum foil provides the best MVTR of about 0.0003. Multiple layers of Aluminized Polyester can provide 0.02 to about 0.005.

Puncture Resistance is an important feature for barrier bags. Sharp tray edges may tear through bags with low puncture resistance.

3M is a trademark of 3M Company.

of their respective owners.

All other trademarks herein are the property

#### R O D U C T D ATA SHEET

# Dri-Shield 2000 Moisture Barrier Bag ALUMINIZED

**PRODUCT** MOISTURE BARRIER BAG, ALUMINIZED

ITEM NUMBER 700(W")(L")

DATASHEET 1102-A 98-0799-1075-2 3M Electronic Solutions Division 6801 River Place Blvd Austin, TX 78726-9000 US and Canada: 866-722-3736

Fax: 866-722-3735 Intl: 919-718-0000; Fax: 919-774-8174

email: 3Mstaticinfo@mmm.com; www.3Mstatic.com © 3M 2011. All rights reserved



# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## 3M:

<u>7001020</u> <u>7001024</u> <u>7001218</u> <u>7001430</u> <u>7001719</u> <u>7001818</u> <u>700424</u> <u>70046</u> <u>700530</u> <u>700624</u> <u>700630</u> <u>70068</u> 700810 700812 7001518 7001824 7001012 7001618 7001216 700610 7001030 70035