




Chicago Miniature Lighting, LLC

Lighting the world since 1910

7018X Series Bicolor SMT LEDs

7018X Series Bicolor SMT LEDs

DESCRIPTION AND FEATURES



Color Combinations:

- Red/Green
- Green/Yellow

Surface Mount Technology

- Tape and reel packaged for high-speed autoinsertion.
- Convection and vapor-phase reflow compatible.
- Compact form enables high density placement.
- Packaged 4000 pieces per reel.

Leading Edge LED Optoelectronic Performance

- Consistent high brightness.

Exceptional Reliability

- Stringent process controls assure quality.
 - Extensive qualification testing to meet strictest requirements.
 - Designed to permit easy post-reflow solder joint inspection.
- Solder pad geometry on page 1-X1.

ELECTRO-OPTICAL CHARACTERISTICS AND RATINGS

PART NUMBER	7018X1/5	7018X5/7
Output Color	Red/Green	Green/Yellow
Diffusion	Diffused	Diffused
Package Color	Clear	Clear
Test Current (mA)	20	20
Forward Voltage Typ. (V)	2.1	18
Forward Voltage Max. (V)	2.8	28
Luminous Intensity Min. (mcd)	4.5	9
Luminous Intensity Typ. (mcd)	6.4	16
Luminous Intensity Max. (mcd)	-	-
Peak Wavelength (nm)	560	580
Viewing Angle (degrees)	120	110
Power Dissipation (mW)	70	70
Storage Temperature (°C)	-40 to +100	-40 to +100
Operating Temperature (°C)	-30 to +85	-30 to +85
Peak Forward Current Max. (1µs @ 0% duty cycle) (mA)	60	60
Reverse Voltage (IR=100µA) (V)	4	4
Lead Solder Time @260°C	5	5

147 Central Avenue
Hackensack, NJ 07601
Phone: (201) 489-8989
Fax: (201) 489-6911

18703 Dix Toledo Road
Brownstown, MI 48193

Saret Zone Franca, Edificio B
Alajuela Costa Rica

E-mail: sales@chml.com • Web Site: www.chml.com

Chicago Miniature Lighting, LLC reserves the right to make specification revisions that enhance the design and/or performance of the product

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Chicago Miniature:

[7018X5/7-100](#) [7018X1/5-100](#)