Shock-Safe Fuseholder, 10.3 x 38 mm, Fingergrip



600 VAC · 4.5 W/25 A25 A (UL/CSA)

Approvals and Compliances

Description	Weblinks
- Screw type fuse carrier	pdf datasheet, html-datasheet, General Product Information, Packaging
	details, Distributor-Stock-Check, Detailed request for product, Microsite

Technical Data				
Fuse-Link	10.3 x 38 mm			
Mounting	Panel Mount, Front Side			
Terminal	Quick-Connect 6.3 x 0.8 mm			
Rated Voltage	600 VAC			
Rated current	25A (UL/CSA)			
Rated Power Acceptance IEC	4.5W / 25A @ Ta 23°C			
Degree of Protection	IP 40 / IP 67			
Admissible Ambient Air Temp.	-40 °C to 85 °C			
Climatic Category	40/085/21 acc. to IEC 60068-1			
Material: Socket	Thermoset, black			
Unit Weight	48 g			
Storage Conditions	0°C to 60°C, max. 70% r.h.			
Product Marking	Type, Rated Voltage, Rated current			

Soldering Methods	Iron	
	Soldering Profile	
Contact Resistance	$<$ m Ω at 20 mV	
Panel Thickness	max 4mm	

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 23530P

Approval Logo	Certificates	Certification Body	Description	
A	UL Approvals	UL	UL File Number: E41738	
®	CSA Approvals	CSA	CSA Certification Record: 23151	
NNO				

Product standards

Product standards that are referenced

Organization	Design	Standard	Description
(UL)	Designed according to	UL 4248-1	Fuseholder general requirements
CSA Group	Designed according to	CSA C22.2 no. 4248.1	Fuseholder general requirements

Application standards

Application standards where the product can be used

Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 60950	IEC 60950-1 includes the basic requirements for the safety of information technologyequipment.


Compliances

The product complies with following Guide Lines

The product complies that relief may earlied Error			
Identification	Details	Initiator	Description
C€		SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
ROHS	RoHS	SCHURTER AG	EU Directive RoHS 2011/65/EU
50	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimension [mm]

-d 63 mm





Mounting holes

All Variants

Holder	Сар	Degree of Pro- tection	NNO Reference	Order Number
•	Fingergrip	IP 40	● ● 23530P	7093.2510
•	Fingergrip	IP 67	● 23530JJP	7093.2540

Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check/Stock-Check/Stock-Check/Stock-Check/Stock-Check/Stock-Check/Stock-Check/Stock-Check-Check/Stock-Check-Check/Stock-Check-Check-Check/Stock-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-Check-

Packaging Unit Bulk (10 pcs.)

product selected for their own applications.