

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

7440680180

Bezeichnung :

SPEICHERDROSSEL WE-TPC 8012

description :


POWER-CHOKE WE-TPC 8012



WÜRTH ELEKTRONIK

DATUM / DATE : 2009-04-21

A Mechanische Abmessungen / dimensions:




● start of winding

	8x8x1,20	
A	8,0 ± 0,3	mm
B	8,0 ± 0,3	mm
C	1,10 ± 0,10	mm
D	3,2 typ.	mm
E	2,4 typ.	mm
F	1,0 typ.	mm

C Lötpad / soldering spec.:

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Induktivität / inductance	100 kHz / 10mA	Lo	18,0	μH	±20%
DC-Widerstand / DC-resistance	@ 20 °C	R _{DC} typ.	302	mΩ	typ.
DC-Widerstand / DC-resistance	@ 20 °C	R _{DC} max.	325	mΩ	max.
Nennstrom / rated Current	ΔT = 40 K	I _N	0,90	A	typ.
Sättigungsstrom / saturation current	ΔL/L < 35%	I _{sat}	0,75	A	typ.
Eigenres.-Frequenz / self-res.-frequency	@ 20 °C	SRF	14,0	MHz	typ.



D Prüfgeräte / test equipment:

WAYNE KERR 3260B für/for L₀; I_{SAT}

Agilent N5776A für/for I_{DC};

Metra Hit 271 für/for R_{DC};

E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%

Umgebungstemperatur / temperature: +20 °C

F Werkstoffe & Zulassungen / material & approvals:

Basismaterial / base material: Ferrit/ ferrite

Draht / wire: Class H

Endoberfläche / finishing electrode: Ag/Ni/Sn

G Eigenschaften / general specifications:

Betriebstemp. / operating temperature: -40 °C - +125 °C

Umgebungstemp. / ambient temperature: -40 °C - +85 °C

It is recommended that the temperature of the part does not exceed 125 °C under worst case operating conditions.

Freigabe erteilt / general release:	Kunde / customer			
Datum / date	Unterschrift / signature			
	Würth Elektronik			
		ME	Version 1	09-04-21
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400

http://www.we-online.de

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

7440680180

Bezeichnung :

SPEICHERDROSSEL WE-TPC 8012

description :


POWER-CHOKE WE-TPC 8012



WÜRTH ELEKTRONIK

DATUM / DATE : 2009-04-21

H Induktivitätskurve / Inductance curve:



Freigabe erteilt / general release:	Kunde / customer				
Datum / date	Unterschrift / signature				
	Würth Elektronik				
			ME	Version 1	09-04-21
Geprüft / checked	Kontrolliert / approved		Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
http://www.we-online.de

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

7440680180

Bezeichnung :

SPEICHERDROSSEL WE-TPC 8012

description :

POWER-CHOKE WE-TPC 8012




WÜRTH ELEKTRONIK



DATUM / DATE : 2009-04-21

I Rollenspezifikation / tape and reel specification:

Gurtspezifikation / Tape specification:



A	4,00 ± 0,1	mm
B	12,00 ± 0,1	mm
C	16,0 ± 0,3	mm



Rollenspezifikation / Reel specification:		
a	178,0 ± 2,0	mm
b	21,00 ± 0,8	mm
c	13,00 ± 0,5	mm
d	50,00 ± 1,0	mm

Freigabe erteilt / general release:	Kunde / customer			
Datum / date	Unterschrift / signature			
	Würth Elektronik			
Geprüft / checked	Kontrolliert / approved	ME	Version 1	09-04-21
		Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400

<http://www.we-online.de>