

Item no.: 745-801  
 Product description: MODULAR PCB TERMINAL BLOCK; 2 SOLDER PINS / POLE; 1 POLE; PIN SPACING 5 MM / 0.197 IN; FRONT-ENTRY; CAGE CLAMP®CONNECTION



Packing unit 200 2\*100 pieces

Pin spacing from	5 mm
Pin spacing from	0.197 in
Cross section from [mm²]	0.08 mm²
Cross section to [mm²]	4 mm²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP® CONNECTION
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	20 A
Weight	2.01 g
Color	gray
Wiring type	Front-entry
No. of connection Points	1
No. of potentials	1
Height	19 mm
Height	0.748 in
Width	5 mm
Width	0.197 in
Depth	22.9 mm
Depth	0.902 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
745-801	CCA	NL5831	250	32	0,08-4
745-801	cURus	E45172	300	20	28-12
745-801	ENEC15	DK131096-01	250	20	0,5-4
745-801	KEMA	2076500.01	250	32	0,08-4

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected