



PCB D-SUB CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

09 PLUG SP/AP SCRLK

AMPLIMITE | AP , SP

745071-4

TE Internal Number: 745071-4
Alias ID: 1218365

5 of 6 EU RoHS/ELV Compliant
[Find Compliant Alternatives](#)

Connector Style **Plug**

Centerline (in) **.108**

Number of Positions **9**

Number of Rows **2**

Shell Size **1**

Product Drawings

[PLUG ASSEMBLY, SIZE 1, 9 POSN, VERTICAL, AMPLIMITE HD-20](#)

PDF (TIFF AVAILABLE)
English

[PLUG ASSEMBLY, SIZE 1, 9 POSN, VERTICAL, AMPLIMITE HD-20](#)

PDF (TIFF AVAILABLE)
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_745071-4_12122015150_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Plug

Shell Size

1

Profile

Standard

	PCB Mounting Orientation	Vertical
	Grounding Straps	Without
	Shell Type	All Plastic
	Grounding Indents	Without
	Applies To	Printed Circuit Board
	Sealed	No
	Product Type	Connector
<hr/>		
Configuration Features	Number of Positions	9
	Number of Rows	2
	Preloaded	Yes
<hr/>		
Body Features	Plastic	Yes
	Female Screwlock Material	Brass
	Female Screwlock Plating Material	Nickel over Copper Flash
	Color Code	None
	Post Size	.66 mm [.026 in]
<hr/>		
Contact Features	Contact Shape	Round
	Solder Tail Contact Plating Material	Tin-Lead over Nickel
	Contact Base Material	Brass
	Contact Mating Area Plating Thickness (µin)	30
	Contact Mating Area Plating Material	Gold Flash over Palladium Nickel, Gold
<hr/>		
Termination Features	Termination Post Length	4.32 mm [.17 in]
	Grounding Clips	Without
<hr/>		
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	With
	PCB Mount Retention Type	Mounting Holes
	Mating Connector Lock	With
	Mating Connector Lock Type	Female Screwlocks, Fixed
	Panel Mount Retention	Without
	Mounting Hole Diameter	3.05 mm [.12 in]
<hr/>		
Housing Features	Centerline (in)	.108
	Mounting Hole Diameter	3.05 mm [.12 in]

Housing Color	Black
Housing Material	Polyester

Dimensions	PCB Thickness (Recommended)	2.36 – 3.18 mm [.093 – .125 in]
------------	-----------------------------	--

Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	UL E28476

Packaging Features	Packaging Method	Tube
	Packaging Quantity	17

Other	Comment	Plugs are preloaded with size 20 DF posted pin contacts
-------	---------	--

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

Products - 3 Results

[View All](#)

Compare 0/10

Relation Type

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - IDC D-Sub Connectors
AMPLIMITE I HDF for Flat Ribbon Cable
**09 POS HDF RCPT, AP,
LEAD FREE - 1658609-4**
TE INTERNAL NUMBER: 1658609-4

Active

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Number of Positions **9**

Number of Rows **2**

Preloaded **Yes**

Contact Size **20**

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - IDC D-Sub Connectors
AMPLIMITE I HDF for Flat Ribbon Cable
**09 POS HDF RCPT, AP,
LEAD FREE - 1658609-4**

Always EU RoHS/ELV Compliant



09 POS HDF RCPT, AP,
LEAD FREE - 1658614-4
TE INTERNAL NUMBER: 1658614-4

✓ Active

Connector Style **Receptacle**

Number of Positions **9**

Number of Rows **2**

Preloaded **Yes**

Contact Size **20**

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - IDC D-Sub Connectors
AMPLIMITE I HDE (IDC) Insulation

09 HDE AP RECEPT,
LEAD FREE - 745201-7
TE INTERNAL NUMBER: 745201-7

✓ Active

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Number of Positions **9**

Number of Rows **2**

Preloaded **Yes**

Contact Size **20**

