


Item no.: 769-634  
 Product description: Plug WITH STRAIGHT SOLDER PIN MATING DIRECTION PERPENDICULAR TO PCB 1 X 1 MM / 0.039 X 0.039 IN PIN SPACING 5 MM / 0.197 IN 4 POLE



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	4
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Weight	4.31 g
Color	gray
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	4
Height	22.2 mm
Height	0.874 in

Width	21.2 mm
Width	0.835 in
Depth	18.3 mm
Depth	0.72 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
769-634	ABS	05-HG476175/3-PDA	500	32	4
769-634	CSA	154112-1101144	300	20	28-12
769-634	KEMA	2077750.01	500	32	4
769-634	UR	E45171	600	20	16-12
769-634	UR	E45172	300	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected