

Series 77 Shrink Boots Boot Selection Guide



Lipped Shrink Boots for Use with Boot Adapters:



Standard Boots

Pages B-1 - B-5
770-001S, 770-003S

Available in ten sizes, standard boots fit adapters from .250" (6.35) to 2.470" (62.70) diameter.



Short Boots

Pages B-6 - B-10
770-002S, 770-004S

Available in seven sizes, short boots fit adapters from .450" (11.43) to 2.470" (62.70) diameter. Use where space is limited.



Long Tail Boots

Pages B-11 - B-15
770-006S

Available in ten sizes, long tail boots fit adapters from .500" (12.70) to 3.200" (81.30) diameter, providing added protection to open wire bundles or extra-long stripped cable ends.



High Ratio Boots

Pages B-16 - B-20
770-007S

Available in four sizes, high ratio boots fit adapters from .525" (13.34) to 1.650" (41.91) diameter. High ratio boots are used when the wire bundle or cable is much smaller diameter than normal.



90° and 45° Angle Boots

Pages C-1 - C-10
770-001A, 770-003A,
770-001B, 770-003B

Available in eight sizes, 90° and 45° angle boots fit adapters from .350" (8.89) to 2.550" (64.80) diameter.

Lipless Boots for Direct Connector Attachment:



Standard Boots

Pages D-1 - D-4
770-005S

Available in eleven sizes, standard boots fit connectors from .250" (6.35) to 3.200" (81.30) diameter.



Right Angle Boots

Pages E-1 - E-4
770-005A

Available in eight sizes, right angle boots fit connectors from .250" (6.35) to 2.000" (50.80) diameter.



Convolute Boots

Pages F-1 - F-3
770-022C

Available in six sizes, convolute boots fit adapters from .250" (6.35) to 1.500" (38.10)

Multi-Leg "Y" and "T" Transitions:



"Y" Transitions

Pages G-1 - G-4
770-009Y, 770-010Y

Available in seven sizes and two body styles (low profile and wide body), "Y" transitions fit cables from Ø .200" (5.08) to .400" (10.16)



"T" Transitions

Pages G-5 - G-8
770-011T, 770-012T

Available in four sizes and two body styles (low profile and wide body), "T" transitions fit cables from Ø .100" (2.54) to 1.250" (31.75)



1:3 and 1:4 Transitions

Pages G-9 - G-14
770-013, 770-014, 770-015

Available in 1 to 3 (low profile and wide body) and 1 to 4 (wide body), multi-leg transitions fit cables from Ø .200" (5.08) to 2.00" (50.8)