



MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

4P MOD II SHROUDED HEADER, RT ANG.

AMPMODU | AMPMODU Headers

826468-4

TE Internal Number: 826468-4

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **4**

PCB Mounting Orientation **Right Angle**

Product Drawings

[AMPMODU II STIFTLISTE 90DEG EINREIHIG](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_826468-4_021820151144_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Right Angle

Connector Type

Header

	Row-to-Row Spacing	2.54 mm [.1 in]
	Stabilizers	Without
	Strain Relief	Without
	Board Standoff	Without
	Profile	Standard
	Product Type	Connector
	Gasket	Without
<hr/>		
Configuration Features	Number of Positions	4
	Number of Rows	1
	Selectively Loaded	No
<hr/>		
Electrical Characteristics	Dielectric Withstanding Voltage	750 V
<hr/>		
Body Features	Post Size	.64 mm [.025 in]
<hr/>		
Contact Features	Contact Shape	Round
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Mating Area Plating Thickness (µm)	5
	Contact Mating Area Plating Material	Gold
	Contact Protection Type	Shrouded
<hr/>		
Termination Features	Termination Post Length	3.2 mm [.1259 in]
	Termination End Plating Material	Tin
	Termination End Plating Thickness (µm)	3
	Termination Method to PC Board	Surface Mount, Through Hole
<hr/>		
Mechanical Attachment	PCB Mount Retention	Without
	Mating Connector Lock Type	Detent Latching
	Panel Mount Retention	Without
	Mating Alignment	With
	Mating Connector Lock	With
	Mating Alignment Type	Polarization
<hr/>		
Housing Features	Centerline	2.54 mm [.1 in]

Housing Features	Centerline	2.94 mm [.116 in]
	Housing Color	Black
	Housing Material	Polyester-GF
	Housing Style	Open End / Open End
Dimensions	Mating Post Length	6.7 mm [.264 in]
Usage Conditions	Operating Temperature Range (°C)	-55 – 105
	High Temperature Housing	Yes
Operation/Application	High Speed Serial Data Connector	No
Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, CUL E28476
Packaging Features	Packaging Quantity	100
	Packaging Method	Carton
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT


SURFACE MOUNT RESISTORS



CPF 0603 26K7 1% 50PPM
1K RL
CPF0603F26K7C1

[Save to List](#)
[Find Similar Products](#)

THROUGH-HOLE RESISTORS



SQM5 1K5 5% (METAL FILM)
SQMR51K5J

[Save to List](#)
[Find Similar Products](#)

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



6P MOD II SHROUDED HEADER, RT ANG.
826468-6

[Save to List](#)
[Find Similar Products](#)

SURFACE MOUNT RESISTORS



CPF 0603 3K4 0.1% 25PPM
1K RL
CPF0603B3K4E1

[Save to List](#)
[Find Similar Products](#)