



For more Information  
please call

1-800-Belden1



## General Description:

19 AWG solid .037" silver-coated copper-covered steel conductor, plenum, TFE Teflon® insulation, double silver-coated copper braid shields (95% coverage), FEP jacket.

## Physical Characteristics (Overall)

### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	19	Solid	SCCCS - Silver-coated Copper-covered Steel	0.037

Total Number of Conductors: 1

### Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)
Teflon®	TFE - Tetrafluoroethylene	.116

### Outer Shield

Outer Shield Material:

Layer #	Type	Outer Shield Material	Coverage (%)
1	Braid	Silver-coated Copper	95.000
2	Braid	Silver-coated Copper	95.000

### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
FEP - Fluorinated Ethylene Propylene

### Overall Cable

Overall Nominal Diameter: 0.195 in.

## Mechanical Characteristics (Overall)

Operating Temperature Range: -70°C To +200°C

UL Temperature Rating: 200°C

Bulk Cable Weight: 42 lbs/1000 ft.

Max. Recommended Pulling Tension: 146 lbs.

Min. Bend Radius/Minor Axis: 2 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
Military Specification:	MIL-DTL-17, M17/60
RG Type:	142/U

**Flame Test**

CSA Flame Test: FT6

**Plenum/Non-Plenum**

Plenum (Y/N): Yes

**Electrical Characteristics (Overall)**

**Nom. Characteristic Impedance:**

Impedance (Ohm)  
50

**Nom. Inductance:**

Inductance (µH/ft)  
.067

**Nom. Capacitance Conductor to Shield:**

Capacitance (pF/ft)  
29.0

**Nominal Velocity of Propagation:**

VP (%)  
70%

**Nominal Delay:**

Delay (ns/ft)  
1.48

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)  
19.3

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)  
2.3

**Maximum VSWR:**

Freq. (MHz)	Max. VSWR
50	1.11
400	1.14
1000	1.17
3000	1.33
8000	1.33

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
10	1.1
50	2.6
100	3.8
200	5.4
400	7.9
700	10.7
900	12.3
1000	13.1
2000	19.3
3000	24.2
5000	32.6
8000	43.2

**Max. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
50	4
100	5.5
400	11.7
1000	19
3000	35
8000	66

**Max. Power Rating:**

Freq. (MHz)	Rating (W)
50	3500
100	2400
400	1100
1000	650
3000	330

8000	180
------	-----

Max. Operating Voltage - UL:

<b>Voltage</b>
150 V RMS

### Misc. Information (Overall)

### Notes (Overall)

**Notes:** Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
84142 001100	100 FT	5.000 LB	BROWN		M17/60-RG142 COAX
84142 0011000	1,000 FT	44.000 LB	BROWN	C E	M17/60-RG142 COAX
84142 001500	500 FT	22.500 LB	BROWN	C E	M17/60-RG142 COAX

**Notes:**

C = CRATE REEL PUT-UP.

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

Revision Number: 6    Revision Date: 04-04-2014

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[84142 001500](#) [84142 0011000](#) [84142 001100](#)