



Polyester Film Tape

850

Technical Data

July, 2011

Product Description 3M™ Polyester Film Tape 850 can generally be used for splicing and applications where chemical resistance and/or clean removal is necessary. The silver backing is a transparent polyester with a thin layer of aluminum.

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Polyester	Acrylic (transparent)	Transparent, Red, Black, White, Silver	72 yds. (66 m)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

ASTM Test Method		
Adhesion to Steel:	30 oz./in. width (33 N/100 mm)	D-3330
Silver:	42 oz./in. width (46 N/100 mm)	D-3330
Tensile Strength at Break:	28 lbs./in. width (491 N/100 mm)	D-3759
Elongation at Break:	120%	D-3759
Backing Thickness:	0.9 mil (0.02 mm)	D-3652
Total Tape Thickness:	1.9 mils (0.05 mm)	D-3652
Water Vapor Transmission Rate:	1.6 gms. H ₂ O/100 sq. in./24 hrs. (24.8 g/m ² /24 hrs.)	D-3833
	Silver: 0.9 gms. H ₂ O/100 sq. in./24 hrs. (7.75 g/m ² /24 hrs.)	D-3833
Temperature Use Range:	-60°F to 300°F (-50°C to 150°C)	

Features

- Prolonged exposure to sunlight or hot caustics will cause backing to become brittle and lose tensile strength.
- Thin, high strength polyester film helps reduce failures due to breakage while meeting low caliper requirements.
- Chemical and solvent resistance to help reduce rejects produced from chemical and solvent attack.
- Abrasion resistant to help protect surface from abrasion and rough handling.

3M™ Polyester Film Tape

850

Application Ideas

Transparent, Red, Black, White:

- Splicing and web defect marking.
- Sealing, labeling and protecting.
- Positive film striping (transparent).
- Decorative edging.
- Tape hinge.

Silver:

- Post splicing movie film.
- Deflect flagging where reflective sensing is required.
- Decorative striping and die cutting.
- Decorative edging.

Storage

Store under normal conditions of 60° to 80°F (16° to 21°C) and 40 to 50% R.H. in the original carton.

Shelf Life

To obtain best performance, use this product within 18 months from date of manufacture.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2008

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2008 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2011 70070776433 (7/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[3M:](#)

[850-Black-1/2"x72yd-Bulk](#) [850-Black-3/4"x72yd-Bulk](#) [850-Black-2"x72yd-Bulk](#) [850-Black-1"x72yd-Bulk](#) [850-Red-1"x72yd](#) [850-Red-1-1/4"x72yd](#) [850-Red-2"x72yd](#) [850-Silver-3/8"x72yd-Bulk](#) [850-Silver-1/2"x72yd-Bulk](#) [850-Silver-3/4"x72yd-Bulk](#) [850-Silver-1"x72yd-Bulk](#) [850-Silver-2"x72yd-Bulk](#) [850-Silver-3"x72yd-Bulk](#) [850-Trans-3/8"x72yd-Bulk](#) [850-Trans-1/2"x72yd-Bulk](#) [850-Trans-3/4"x72yd-Bulk](#) [850-Trans-1"x72yd-Bulk](#) [850-Trans-1-1/2"x72yd-Bul](#) [850-Trans-2"x72yd-Bulk](#) [850-Trans-3"x72yd-Bulk](#) [850-White-1/2"x72yd-Bulk](#) [850-White-1"x72yd-Bulk](#)