



Active

PRODUCT DRAWING
English

TE CONNECTIVITY (TE)

52 MODIV HSG COMP DR .100 EARS

AMPMODU | AMPMODU IV/V

86264-4

TE Internal Number: 86264-4

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **52**

Number of Rows **2**

Row-to-Row Spacing **2.54 mm [.1 in]**

Product Drawings

[CONNECTOR, MOD IV, CRIMP SNAP-IN, DOUBLE ROW, .100X.100 CENTERS](#)

PDF (TIFF AVAILABLE)

English

[CONNECTOR, MOD IV, CRIMP SNAP-IN, DOUBLE ROW, .100X.100 CENTERS](#)

PDF (TIFF AVAILABLE)

English

Product Specifications

Product Specification

[AMPMODU Mod 1/2 Wire To Board Standard Pressure Contact Interconnection System](#)

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Row-to-Row Spacing	2.54 mm [.1 in]
Connector Style	Receptacle
Glow Wire Rating	Standard Part - Not Glow Wire
Strain Relief	Without
Connector Type	Housing
Product Type	Connector

Configuration Features

Number of Positions	52
Number of Rows	2

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	----------------

Contact Features	Contact Current Rating (A)	3
	Contact Type	Socket
	Contact Base Material	Beryllium Copper
Termination Features	Termination Method to Wire/Cable	Crimp
Mechanical Attachment	Mating Connector Lock	Without
	Mating Alignment	Without
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Nylon - GF
	Housing Configuration	Both Ends Closed
	Housing Color	Black
Dimensions	Length	78.74 mm [3.1 in]
	Height	6.1 mm [.24 in]
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	1
	Packaging Method	Package

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)