
Item no.:	869-321
Product description:	CENTER TERMINAL BLOCK LATERAL MARKING WITHOUT SNAP-IN MOUNTING FOOT max. insulation diameter 4.4 mm FRONT-ENTRY CAGE CLAMP® COMPACT CONNECTION HORIZONTAL TYPE FOR SHEET THICKNESS 0.6-1.2 MM Fixing hole 3.5+0.1 mm Ø



Packing unit 100 pieces

Product group	16 (RAIL MOUNTED TERMINAL BLOCK WITH CCC)
Cross section [mm²]	0.08 - 2.5 mm²
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP® COMPACT CONNECTION
Cross section [mm²]	0.08 - 4 mm²
Cross section [AWG]	28 - 12 AWG
Wiring method	f
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	24 A
Weight	4 g
Color	gray
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	1
Height	27.6 mm
Height	1.086 in
Width	5 mm
Width	0.197 in
Depth	33.4 mm
Depth	1.315 in



Strip length from	6 mm
Strip length to	7 mm
Strip length	0.26 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
869-321	ABS	05-HG476175/1-PDA	500	24	2,5
869-321	CCA	NL5837	500	24	2,5
869-321	cURus	E45172	300/600	20/5	28-12
869-321	DNV	E7570	500	24	2,5
869-321	KEMA	2082859.05	500	24	2,5

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected