




Product Name:	UL1213 24AWG
Product Discription:	UL1213 24AWG
Specification No.:	
Customer's Name:	

Description					
Rated Voltage:		Not specified			
Rated Temperature:		105℃, 60 ℃ Oil			
Reference Standard:		UL758			
Cross Section					
					
Marking					
No marking on the cable jacket, have UL label on the Reel.					
Applications					
Internal wiring where not subjected to mechanical abuse, Oil Resistant 60 deg C.					
Revisions					
Version	Description	Drawn by	Approved by	Date	
0	New document issue	Danniel	Jason	24/04/2015	
Construction					
Conductor		Stranded Sliver plated copper			
Size(AWG)		24			
Construction(±0.008mm)		7/0.203			
Stranded Dia.(mm)Ref.		0.61			
Insulation Material		PTFE			
Insulation Color		ANY COLOR			
Ave Thickness(mm)		0.2			
Insulation Dia.(±0.08mm)		1.09			
Remark: 8739696 Grey 8739692 Orange 8739699 Yellow 8739706 Violet 8739680 Brown					
Characteristics					Customer Approve
Test Item			Standard Value		Seal & Stamp
Test Material			PTFE(ROHS)		
Insulation resistance(20℃ MΩ*m			1000		
Vol. Tesr(AC.V.60S)(V)			2000		
Flammability Test			Horizontal flame		
Max.DC Resistance(20℃ Ω/km)			78.4(MAX)		
					Signature:
					Date: