

## Datasheet




**ENGLISH**

### New 3.5mm Plug 8A 2 Way

RS Stock 874-5102



### Dimensions: (mm)





## Specifications

ENGLISH

### Electrical

Standard	UL	IEC
Rated voltage	300V	250V
Rated current	8A	10A
Contact resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Wire range	28~16AWG	1mm <sup>2</sup>
Wrth standing voltage	AC 2000V/1 Min	

### Mechanical

Torque	0.4Nm(3.6Lb.in)
Steip Length	7-8mm
<b>Dimensions</b>	
Pitch	3.5mm
Poles	2~24p
Material	
Housing	PA66, UL94V-0
Clamp	Phosphor bronze,Ni plated
Wire guard	Stainless steel

	linear dimension(Tolerances Standard GB/T 14486-2008)												=	-	□	//	⊥
variable range	over 6 to 6	over 10 to 10	over 18 to 18	over 30 to 30	over 50 to 50	over 80 to 80	over 120 to 120	over 160 to 160	over 200 to 200	over 250 to 250	all	over 5 to 5	over 30 to 30	over 120 to 120			
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.43	±0.57	±0.72	±0.88	±1.05	±1.25	0.5	0.025	0.06	0.12	0.4	