





① WILL ALSO MATE W/OTHER CONNECTORS WHICH ARE COMPATIBLE WITH THE 066 & .150 END DIMS.

2 OBSOLETE PART NUMBER

**3 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING
PER D.RENAUD/D.SINISI**

3	OBSOLETE	3.132	3.032	2.806	.106	2.890	.190	3.804	3.604	3.200	2.900	29	60	2-87496-6
		3.032	2.932	2.706	↑	2.790	↑	3.704	3.504	3.100	2.800	28	58	2-△↑ -5
		2.932	2.832	2.606		2.690		3.604	3.404	3.000	2.700	27	56	2-△ -4
		2.832	2.732	2.506		2.590		3.504	3.304	2.900	2.600	26	54	2-△ -3
		2.732	2.632	2.406		2.490		3.404	3.204	2.800	2.500	25	52	2-△ -2
		2.532	2.432	2.206		2.290		3.204	3.004	2.600	2.300	23	48	2-△ -1
		2.432	2.332	2.106		2.190		3.104	2.904	2.500	2.200	22	46	2-△ -0
		2.332	2.232	2.006		2.090		3.004	2.804	2.400	2.100	21	44	1-△ -9
		2.232	2.132	1.906		1.990		2.904	2.704	2.300	2.000	20	42	1-△ -8
3	OBSOLETE	2.132	2.032	1.806		1.890		2.804	2.604	2.200	1.900	19	40	↑ -7
		2.032	1.932	1.706		1.790		2.704	2.504	2.100	1.800	18	38	1-△ -6
		1.932	1.832	1.606		1.690		2.604	2.404	2.000	1.700	17	36	1-△ -5
3	OBSOLETE	1.832	1.732	1.506		1.590		2.504	2.304	1.900	1.600	16	34	↑ -4
		1.732	1.632	1.406		1.490		2.404	2.204	1.800	1.500	15	32	1-△ -3
3	OBSOLETE	1.632	1.532	1.306		1.390		2.304	2.104	1.700	1.400	14	30	↑ -2
		1.532	1.432	1.206		1.290		2.204	2.004	1.600	1.300	13	28	1-△↑ -1
3	OBSOLETE	1.432	1.332	1.106		1.190		2.104	1.904	1.500	1.200	12	26	1-87496-0
		1.332	1.232	1.006		1.090		2.004	1.804	1.400	1.100	11	24	↑ -9
		1.232	1.132	.906	↓	.990	↓	1.904	1.704	1.300	1.000	10	22	△ -8
		1.132	1.032	.806	.106	.890	.190	1.804	1.604	1.200	.900	9	20	△ -7
		1.032	.932	—	.406	—	.490	1.704	1.504	1.100	.800	8	18	△ -6
		.932	.832	—	.306	—	.390	1.604	1.404	1.000	.700	7	16	△ -5
		.832	.732	—	.306	—	.390	1.504	1.304	.900	.600	6	14	△ -4
		.732	.632	—	.206	—	.290	1.404	1.204	.800	.500	5	12	△ -3
		.632	.532	—	.206	—	.290	1.304	1.104	.700	.400	4	10	↑ -2
		2.632	2.532	2.306	.106	2.390	.190	3.304	3.104	2.700	2.400	24	50	87496-1
		L	K	J	I	G	F	E	D	C	B	A	MD. OF	PART NO

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN INCHES.

TOLERANCES ON:
DECIMALS $\pm .005$
ANGLES $\pm$

MATERIAL
HSG. - GLASS FILLED NYLON
COLOR: BLACK
POST - PHOS. BRONZE

FINISH
POST - .000030 GOLD OVER
.000050 NICKEL

CONTRACT NO

DR D. Meyer 8/21/75

CHK *[Signature]* 8-22-75

APPD *B. Bennett* 8/25/71

APPD
R. Clark 8/25/75

DSGN APPD

OTHER APPD



TE Connectivity

NAME _____

HEADER ASS'Y. MOD II 100x100
CENTERS WITH PIN. PROTECTION
BOTH SIDES & MTG. EARS
(MATES W/ AMP LATCH OR FCC ONE SIDE)
MOD IV OTHER SIDE

SIZE	CODE	IDENT NO	DRAWING NO
------	------	----------	------------

C
SCA

00779

87496

SHEET	1	2
-------	---	---

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[87496-9](#)