




DASH NO.	M CODE	MADE FROM
----------	--------	-----------



- NOTES:
1. INTERFACE PER MIL-STD-348 FIG. 310-2.
 2. MATERIALS:
INSULATORS: TEFLON, ASTM-D4894
CENTER CONTACT: BER. COP., ASTM-B196
ALL OTHER PARTS: STAINLESS STEEL, SAE-AMS-QQ-S-763
 3. FINISHES:
ALL METAL PARTS: HARD GOLD PLATE PER ASTM-B488
 4. ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
FREQUENCY RATING: DC TO 12.4
VOLTAGE RATING: 1000 VRMS

GSD



MOUNTING HOLES

GSD

M39012/94-3001

REVISIONS	
ISSUE	CHANGES
4	CN 32906 E REDRAWN RESTRICTION REMOVED JCA 03/01/91
5	CN 33494 C JCA 10/31/91
6	CN 34192 E KH 10/19/92
7	CN 36001 E ME 01/16/95
8	CN 38473 E TML 01/21/02
9	CN 39474 A DCT 6/13/6
10	CN 39552 C JPK 08/07/06
877-87-1	
SCALE 8:1	
APPROX SURFACE AREA	
USED ON	
REF:	
RCPT, P.C.B., ANG, SMA	
DRAWN JCA	DATE 03/01/91
DESIGN GA	DATE 03/04/91
APPR. DW	DATE 10/26/92
 ELECTRONICS CO., INC. ROCK HILL, SOUTH CAROLINA 29730	
M39012/94-3001	