

# Scotch® Filament Tape 880



Technical Data

May, 2013

## Product Description

Scotch® Filament Tape 880 is a high performance tape reinforced with continuous, polyester yarn filaments that give the tape high tensile strength, high impact resistance and high cut resistance. The polypropylene film backing provides excellent abrasion and moisture resistance. The aggressive packaging grade adhesive is specifically formulated to provide an excellent balance of high initial adhesion and long term holding power to fiberboard, “non-oily” metals, printed and painted surfaces.

## Product Construction

Backing	Adhesive	Reinforcement	Backing Color
Polypropylene film	Pressure sensitive synthetic rubber resin	Polyester yarn	Clear, Black, Blue, or Red

## Typical Physical Properties

**Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	80 oz./in. width (88 N/100 mm width)	D-3330
Tensile Strength:	270 lbs./in. width (4725 N/100 mm width)	D-3759
Elongation at Break:	19%	D-3759
Total Thickness:	7.7 mil (0.20 mm)	D-3652

## Features

- Good handling.
- Printable (clear only).
- Cut and impact resistant.
- High shear adhesion.
- Excellent aging.
- Tough film backing protects the filaments and adhesive to provide longer functional tape performance.
- Good handling characteristics saves time through ease of dispensing and tape application.
- When printed, the tape provides advertising, warning, and labeling capability.
- The polyester filaments resist cutting when tabbing the end lap of metal coils.
- The polyester filaments absorb the shock of rough, high impact handling to keep package secure during shipping.
- High tensile strength allows the use of less tape in many applications and lowers the cost per application.
- Translucency of the clear version allows good clarity of artwork and important messages, even when covered by the tape.
- Adhesive provides good holding under wide range of application conditions with minimum amount of tape.
- Holds instantly with minimum rubdown.
- Boxes remain securely closed through normal warehouse time cycles.

# Scotch® Filament Tape

880

---

## Available Sizes

Standard Widths: 0.35 in. (9 mm), 0.47 in. (12 mm), 0.59 in. (15 mm), 0.71 in. (18 mm), 0.94 in. (24 mm), 1.2 in. (30 mm), 1.4 in. (36 mm) and 1.9 in. (48 mm)

---

Core Size (ID): 3 in. (76.2 mm)

---

Lengths: 60 yds. (55 m)

---

---

## Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended. Rotate your stock.

---

## Shelf Life

To obtain best performance, use this product within 18 months from date of manufacture.

---

## Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

---

## Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

---

## Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

---

## Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

**ISO 9001**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.



### Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (Fax)  
www.3M.com/industrial



Recycled Paper  
40% pre-consumer  
10% post-consumer

Scotch is a registered trademark of 3M.  
Printed in U.S.A.  
©3M 2013 70071002938 (5/13)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[3M:](#)

[880-18mmx55m](#) [880-24mmx55m](#)